

The Complexity of Deciding a Behavioural Pseudometric on Probabilistic Automata

Hongfei Fu

The publications of the Department of Computer Science of *RWTH Aachen University* are in general accessible through the World Wide Web.

<http://aib.informatik.rwth-aachen.de/>

The Complexity of Deciding a Behavioural Pseudometric on Probabilistic Automata

Hongfei Fu

Lehrstuhl für Informatik II
RWTH Aachen, Germany

Email: hongfeifu@informatik.rwth-aachen.de

Abstract. In this paper we study the complexity of computing a behavioural pseudometric on Segala’s probabilistic automata. The pseudometric concerned here stems from a real-valued logic (by Desharnais *et al*) and does not discount the future. We show that the problem whether the pseudometric between two states of a finite probabilistic automata is under a given threshold lies in the intersection of NP and coNP. This result significantly improves the previous PSPACE upperbound (by e.g. van Breugel *et al*).

1 Introduction

In recent years, probabilistic behavioural equivalences have been extensively studied. Many equivalences such as probabilistic bisimulation [LS91,SL95] and probabilistic simulation [JL91,SL95] have been established. And many efficient algorithms have been proposed for these equivalences [BEMC00,CS02]. Here we focus on probabilistic bisimulation. Generally, probabilistic bisimulation is a class of formal notions judging whether two probabilistic systems are behaviourally “equivalent”. In practical problems, they are often used to compare an implementation of a system with the specification of the system, where both the implementation and the specification are modeled by formal probabilistic systems. Furthermore, one can also tackle the state explosion problem by reducing a large probabilistic system to its quotient system w.r.t probabilistic bisimulation. This is because the quotient system is often PCTL- or PCTL*-equivalent to the original one [ASB95,SL95].

However, the notion of probabilistic bisimulation relies on exact probability values and a slight variation of probability values will differentiate two originally equivalent probabilistic systems. In this sense, this notion is not robust. This is drastically the case when a probabilistic system contains physical objects (such as a wire) whose probability values are based on experimental results. In this case, the probabilistic values should not be treated as “exact values”. Even in pure theoretical probabilistic models where probability values are indeed exact, an implementation of the model may still contain probability values which deviate slightly from their original counterparts. Thus, a notion of approximate bisimulation is really needed.

The notion of approximate bisimulation is first considered by Giacalone *et al* [GcJS90]. They defined a pseudometric over the states of a probabilistic transition system. This yields a smooth, quantitative notion of behavioural equivalence. A pseudometric differs from an ordinary metric in that different elements (i.e., states) can have distance 0. The distance between states, a real number between 0 and 1, can be used to express the similarity of the behaviour of the system

started in those states. The smaller the distance, the more alike the behaviour is. In particular, the distance between states is 0 if they are indistinguishable.

Then the study of approximate bisimulation is divided into two directions. One direction is through a study of real-valued logic where the main work is by Josée Desharnais *et al* [DGJP04]. The other is through a study of coalgebra representation of probabilistic transition systems where the main work is by Franck van Breugel *et al* [vBW01b]. They both defined a pseudometric for probabilistic systems where states with zero distance are probabilistic bisimilar [LS91]. Both of the two pseudometrics are classified into future-discounting (*abbr.* FD) and non-future-discounting (*abbr.* nFD) version. In the FD version, differences that appear in the future are discounted and contribute less to the value of the pseudometric. While in nFD version, differences that appear in the future contribute fully to the pseudometric. NFD pseudometrics seems to be a more natural extension of probabilistic bisimulation, as in [Pan09,vBSW07] it is shown that the nFD pseudometric [DGJP04] defined through a real-valued logic can be defined in a style similar to probabilistic bisimulation [LS91]. Also the notion of nFD pseudometrics is important to analyze systems that are expected to run forever. For FD version, efficient approximation algorithms have been obtained on finite-state systems [vBW01a]. However for nFD version, the best-known complexity upperbound (before this paper) is only PSPACE [vBSW07,CHL09].

In this paper, we consider the nFD pseudometric over finite probabilistic automata [SL95] which is an extension of the nFD ones defined in [Pan09,vBSW07]. We show that the problem whether the pseudometric between two given states is under a given threshold lies in $\text{NP} \cap \text{coNP}$, which significantly improves previous PSPACE upperbound [vBSW07,CHL09].

2 Preliminaries

2.1 Finite Probabilistic Automata

In this subsection we define the notion of “finite probabilistic automata”, which corresponds exactly to Segala’s “simple probabilistic automata” [SL95] in the finite setting.

Definition 1 (Probability Distribution). *Let S be a countable set. A function $\mu : S \rightarrow [0, 1]$ is a probability distribution over S if $\sum_{s \in S} \mu(s) = 1$ and $\mu(s) \in \mathbb{Q}$ for all $s \in S$. We denote the set of probability distributions over S by $\mathcal{D}(S)$.*

Definition 2 (Finite Probabilistic Automata). *A finite probabilistic automata (finite PA) \mathcal{T} is a tuple (S, Act, Ω) where*

- S is a finite set of states;
- Act is a finite set of actions;
- $\Omega \subseteq S \times \text{Act} \times \mathcal{D}(S)$ is a finite set of transitions.

We define $\text{Act}^{\mathcal{T}}(s) := \{a \in \text{Act} \mid \exists \mu.(s, a, \mu) \in \Omega\}$ for each $s \in S$. We write $s \xrightarrow{a} \mu \in \Omega$ instead of $(s, a, \mu) \in \Omega$. We omit ‘ \mathcal{T} ’ or ‘ Ω ’ in the notations above if the context is clear.

Finite probabilistic automata extend Markov Chains studied in [vBSW07,Pan09] in the sense that a Labeled Markov Chain can be deemed as a finite probabilistic automata where the transition relation Ω is a function from $S \times \text{Act}$ to $\mathcal{D}(S)$.

2.2 Polyhedra and Linear Programming

We introduce polyhedra and linear programming along [Sch10]. Given a real-valued vector b , we denote b^i to be the i -th entry of b .

Definition 3 (Polyhedra). A subset $H \subseteq \mathbb{R}^n$ is a halfspace iff there is $h \in \mathbb{R}^n$ and $e \in \mathbb{R}$ such that $H = \{x \in \mathbb{R}^n \mid h^T x \leq e\}$. A subset $P \subseteq \mathbb{R}^n$ is a polyhedron iff it is the intersection of a finite number of halfspaces. Equivalently $P \subseteq \mathbb{R}^n$ is a polyhedron iff there is an $m \times n$ matrix A and a vector $b \in \mathbb{R}^m$ such that $P = \{x \in \mathbb{R}^n \mid Ax \leq b\}$, where “ $Ax \leq b$ ” is an abbreviation for “ $(Ax)^i \leq b^i$ for all $1 \leq i \leq m$ ”.

Remark 1. Informally, a polyhedron is a finite intersection of constraints of the form $h^T x \leq e$. Note that constraints such as $h^T x \geq e$ or $h^T x = e$ are covered, since “ $h^T x \geq e$ ” can be rewritten as “ $(-h)^T x \leq -e$ ” and “ $h^T x = e$ ” is equivalent to “ $h^T x \leq e$ and $h^T x \geq e$ ”.

An important concept to characterize polyhedra is the notion of vertices.

Definition 4 (Vertex). Let P be a polyhedron. A point $z \in P$ is a vertex iff there does not exist points $x, y \in P$ and $\lambda \in [0, 1]$ such that $x \neq z$, $y \neq z$ and $z = \lambda \cdot x + (1 - \lambda) \cdot y$.

The following theorem states that vertices of a polyhedron can be characterized by full-rank rows of the specifying matrix, whose proof can be found in [Sch10, Theorem 2.2].

Theorem 1. Let $P = \{x \in \mathbb{R}^n \mid Ax \leq b\}$ be a polyhedron in \mathbb{R}^n and $z \in P$. Define the matrix A_z to be the submatrix of A consisting of all the row vectors h_i of A for which $h_i z = b^i$. Then z is a vertex of P iff $\text{rank}(A_z) = n$.

Definition 5 (Linear Programming). A linear programming problem (LP) is specified by its type as well as an $m \times n$ matrix A and two vectors $b \in \mathbb{R}^m, c \in \mathbb{R}^n$. There are two types of LP’s: MAX-LP and MIN-LP, whose forms are as follows:

MAX-LP	MIN-LP
maximize $c^T x$	minimize $c^T x$
subject to $Ax \leq b$	subject to $Ax \leq b$

Let Γ be an LP (either a MAX-LP or a MIN-LP) as above. The aim is to compute the optimal value (denoted $\text{OpV}(\Gamma)$) of Γ , which is defined as the maximum (for MAX-LP) or minimum value (for MIN-LP) of the set $\{c^T x \mid x \in \mathbb{R}^n \text{ and } Ax \leq b\}$. The set of feasible solutions of Γ , denoted $\text{Poly}(\Gamma)$, is defined as the polyhedron $\{x \in \mathbb{R}^n \mid Ax \leq b\}$. The set of optimal solutions of Γ , denoted $\text{OpS}(\Gamma)$, is defined as $\{x \in \text{Poly}(\Gamma) \mid c^T x = \text{OpV}(\Gamma)\}$.

Note that the maximum or minimum value can be reached if the supremum or infimum is finite, since $\text{Poly}(\Gamma)$ is a closed set and $x \mapsto c^T x$ is a continuous function.

The following theorem clarifies the relationship between vertices of polyhedra and optimal values of linear programming problems.

Theorem 2. For any LP Γ , if $\text{Poly}(\Gamma)$ is bounded, then the optimal value of Γ is reached at some vertex of $\text{Poly}(\Gamma)$.

Proof. See Theorem 2.3, Theorem 2.4 and Exercise 2.21 in [Sch10].

2.3 Distance Functions and Pseudometrics

In this subsection we introduce distance functions and pseudometrics. Below we fix a set \mathcal{U} .

Definition 6 (Distance Functions, Pseudometrics). *A function $d : \mathcal{U} \times \mathcal{U} \rightarrow [0, 1]$ is a distance function over \mathcal{U} iff $d(u, u) = 0$ for all $u \in \mathcal{U}$. A distance function d is further a pseudometric over \mathcal{U} iff for all $u, v, w \in \mathcal{U}$, $d(u, v) = d(v, u)$ and $d(u, w) \leq d(u, v) + d(v, w)$. We denote the set of distance functions (resp. pseudometrics) over \mathcal{U} by $\mathcal{M}_d(\mathcal{U})$ (resp. $\mathcal{M}_p(\mathcal{U})$).*

In the following we use ‘ κ ’ to indicate either ‘d’ or ‘p’. In this way we can use “ $\mathcal{M}_\kappa(\mathcal{U})$ ” to make arguments shared by both $\mathcal{M}_d(\mathcal{U})$ and $\mathcal{M}_p(\mathcal{U})$.

Definition 7 (The Partial Order). *The binary relation \preceq_κ over $\mathcal{M}_\kappa(\mathcal{U})$ is defined as follows: given $d_1, d_2 \in \mathcal{M}_\kappa(\mathcal{U})$, $d_1 \preceq_\kappa d_2$ iff $d_1(u, v) \geq d_2(u, v)$ for all $u, v \in \mathcal{U}$.*

Clearly, \preceq_κ is a partial order over $\mathcal{M}_\kappa(\mathcal{U})$.

Theorem 3. *$(\mathcal{M}_\kappa(\mathcal{U}), \preceq_\kappa)$ is a complete lattice.*

Proof. The bottom element \perp_κ is determined by: $\perp_\kappa(u, u) = 0$ and $\perp_\kappa(u, v) = 1$ if $u \neq v$; for all $u, v \in \mathcal{U}$. The top element \top_κ is defined by: $\top_\kappa(u, v) = 0$ for all $u, v \in \mathcal{U}$. Given $\mathcal{M} \subseteq \mathcal{M}_\kappa(\mathcal{U})$, the greatest lower bound $\prod \mathcal{M}$ is given by:

$$(\prod \mathcal{M})(u, v) := \sup\{d(u, v) \mid d \in \mathcal{M}\} \text{ for arbitrary } u, v \in \mathcal{U};$$

And the least upper bound $\sqcup \mathcal{M}$ is given by: $\sqcup \mathcal{M} = \prod \{d \in \mathcal{M}_\kappa(\mathcal{U}) \mid \forall d' \in \mathcal{M}. d' \preceq_\kappa d\}$.

3 Distance Functions and Pseudometrics on Probabilistic Automata

In this section we define distance functions and pseudometrics on finite PA. Our pseudometric extends the one on Markov Chains [Pan09,vBSW07], which is defined as a maximum fixed point similar to probabilistic bisimulation [LS91] and shown to be equivalent to the non-future-discounting pseudometric derived from a real-valued logic [Pan09,vBSW07]. Below we fix a finite PA $\mathcal{T} = (S, Act, \Omega)$. We use κ to indicate either ‘d’ or ‘p’.

Definition 8. *Let $d \in \mathcal{M}_\kappa(S)$. Then the element $\Delta(d) \in \mathcal{M}_\kappa(\mathcal{D}(S))$ is given by:*

$$\Delta(d)(\mu, \nu) := \text{OpV}(\Delta_d^{\mu, \nu}), \text{ for all } \mu, \nu \in \mathcal{D}(S)$$

where the LP $\Delta_d^{\mu, \nu}$ is depicted in Tab. 1.

Intuitively, Definition 8 lifts an element of $\mathcal{M}_\kappa(S)$ to an element of $\mathcal{M}_\kappa(\mathcal{D}(S))$. This is however not the original lifting definition. The original one which is derived from the Kantorovich metric [Kan42] is captured by the following definition.

Definition 9. *Given a pseudometric $d \in \mathcal{M}_p(S)$, the pseudometric $\Theta(d) \in \mathcal{M}_p(\mathcal{D}(S))$ is given by: $\Theta(d)(\mu, \nu) := \text{OpV}(\Theta_d^{\mu, \nu})$ for all $\mu, \nu \in \mathcal{D}(S)$, where $\Theta_d^{\mu, \nu}$ is depicted in Tab. 1.*

Table 1. Two Lifting Definitions from $\mathcal{M}_\kappa(S)$ to $\mathcal{M}_\kappa(\mathcal{D}(S))$

$\Theta_d^{\mu,\nu}$	$\Delta_d^{\mu,\nu}$
maximize $\sum_{s \in S} (\mu(s) - \nu(s)) \cdot x_s$ subject to $\bullet \forall s \in S : 0 \leq x_s \leq 1$ $\bullet \forall s, t \in S : x_s - x_t \leq d(s, t)$	minimize $\sum_{s, t \in S} d(s, t) \cdot y_{s, t}$ subject to $\bullet \forall s \in S : \sum_{t \in S} y_{s, t} = \mu(s)$ $\bullet \forall t \in S : \sum_{s \in S} y_{s, t} = \nu(t)$ $\bullet \forall s, t \in S : y_{s, t} \geq 0$

By applying the Kantorovich-Rubinstein Duality Theorem [KR58] (cf. [vBSW07]) or the Duality Theorem of linear programming (cf. [vBW01a]), one can show that the two definitions meet on the pseudometrics over S .

Theorem 4. For any $d \in \mathcal{M}_p(S)$, $\Delta(d) = \Theta(d)$.

The following two lemmas deal with some basic properties related to Definition 8.

Lemma 1 (Monotonicity). For any $d_1, d_2 \in \mathcal{M}_\kappa(S)$, if $d_1 \preceq_\kappa d_2$ then $\Delta(d_1) \preceq_\kappa \Delta(d_2)$.

Proof. Fix arbitrary $\mu, \nu \in \mathcal{D}(S)$. Denote $P := \text{Poly}(\Delta_{d_1}^{\mu,\nu}) (= \text{Poly}(\Delta_{d_2}^{\mu,\nu}))$. By $d_1 \preceq_\kappa d_2$, we have $\sum_{s, t \in S} d_1(s, t) \cdot y_{s, t} \geq \sum_{s, t \in S} d_2(s, t) \cdot y_{s, t}$ for all $\{y_{s, t}\}_{s, t \in S} \in P$. It follows that $\Delta(d_1)(\mu, \nu) \geq \Delta(d_2)(\mu, \nu)$. Then the result follows.

Lemma 2 (Continuity). Let $d \in \mathcal{M}_\kappa(S)$ and $\{d_i\}_{i \in \mathbb{N}}$ for which each $d_i \in \mathcal{M}_\kappa(S)$. If $\lim_{i \rightarrow \infty} d_i(s, t) = d(s, t)$ for all $s, t \in S$, then $\lim_{i \rightarrow \infty} \Delta(d_i)(\mu, \nu) = \Delta(d)(\mu, \nu)$ for all $\mu, \nu \in \mathcal{D}(S)$.

Proof. Fix arbitrary $\mu, \nu \in \mathcal{D}(S)$. Denote $P := \text{Poly}(\Delta_{\mathfrak{d}}^{\mu,\nu})$ where the choice of $\mathfrak{d} \in \mathcal{M}_\kappa(S)$ is irrelevant here. By Theorem 2, for all $\mathfrak{d} \in \mathcal{M}_\kappa(S)$,

$$\Delta(\mathfrak{d})(\mu, \nu) = \min \left\{ \sum_{s, t \in S} \mathfrak{d}(s, t) \cdot y_{s, t} \mid \{y_{s, t}\}_{s, t \in S} \text{ is a vertex of } P \right\}$$

By Theorem 1, the number of vertices of a polyhedron is finite. Then the equation above tells us that $\Delta(\mathfrak{d})(\mu, \nu)$ is continuous on \mathfrak{d} . Thus we have $\lim_{i \rightarrow \infty} \Delta(d_i)(\mu, \nu) = \Delta(d)(\mu, \nu)$.

Then we define a monotone function \mathcal{F}_κ on $\mathcal{M}_\kappa(S)$ as follows.

Definition 10. The function $\mathcal{F}_\kappa : \mathcal{M}_\kappa(S) \rightarrow \mathcal{M}_\kappa(S)$ is given by: for any $d \in \mathcal{M}_\kappa(S)$,

$$\mathcal{F}_\kappa(d)(s, t) := \max_{a \in \text{Act}} \left\{ \max \left(\sup_{s \xrightarrow{a} \mu} \inf_{t \xrightarrow{a} \nu} \Delta(d)(\mu, \nu), \sup_{t \xrightarrow{a} \nu} \inf_{s \xrightarrow{a} \mu} \Delta(d)(\mu, \nu) \right) \right\}$$

for arbitrary $s, t \in S$, where $\inf \emptyset := 1$ and $\sup \emptyset := 0$.

One can prove by definition that \mathcal{F}_κ is indeed a function $\mathcal{M}_\kappa(S) \rightarrow \mathcal{M}_\kappa(S)$ (especially when $\kappa = p$). Furthermore, it can be proved from Definition 10 and Lemma 1 that \mathcal{F}_κ is indeed a monotone function.

Lemma 3. \mathcal{F}_κ is monotone on $\mathcal{M}_\kappa(S)$, i.e., $d_1 \preceq_\kappa d_2$ implies $\mathcal{F}_\kappa(d_1) \preceq_\kappa \mathcal{F}_\kappa(d_2)$.

Remark 2. By definition, $\text{Act}(s) \neq \text{Act}(t)$ implies $\mathcal{F}_\kappa(\mathfrak{d})(s, t) = 1$ and $\text{Act}(s) = \text{Act}(t) = \emptyset$ implies $\mathcal{F}_\kappa(\mathfrak{d})(s, t) = 0$, regardless of the choice of \mathfrak{d} .

Since \mathcal{F}_κ is monotone, it has a greatest fixed point. This is formulated as follows.

Definition 11. Define $\mathbf{d}_\kappa \in \mathcal{M}_\kappa(S)$ to be the greatest fixed point of \mathcal{F}_κ . By Tarski Fixed-Point Theorem, $\mathbf{d}_\kappa = \bigsqcup\{d \in \mathcal{M}_\kappa(S) \mid d \preceq_\kappa \mathcal{F}_\kappa(d)\}$.

The pseudometric \mathbf{d}_p is closely related with strong bisimulation [SL95] on probabilistic automata: s and t are bisimilar iff $\mathbf{d}_p(s, t) = 0$. Here we skip this due to lack of space. One may see [Pan09,vBSW07] for more information. Below we define approximants $\{\mathbf{d}_\kappa^i\}_{i \in \mathbb{N}_0}$ of \mathbf{d}_κ .

Definition 12. The family $\{\mathbf{d}_\kappa^i\}_{i \in \mathbb{N}_0}$ of approximants of \mathbf{d}_κ is inductively defined as follows: $\mathbf{d}_\kappa^0 := \top_\kappa$ (i.e., $\mathbf{d}_\kappa^0(s, t) = 0$ for all $s, t \in S$); $\mathbf{d}_\kappa^{i+1} = \mathcal{F}_\kappa(\mathbf{d}_\kappa^i)$.

Since \mathcal{F}_κ is a monotone function, the sequence $\{\mathbf{d}_\kappa^i\}_{i \in \mathbb{N}_0}$ is decreasing w.r.t \preceq_κ . The following theorem shows that \mathbf{d}_κ is the limitation of the sequence.

Theorem 5. For any $s, t \in S$, $\mathbf{d}_\kappa(s, t) = \lim_{i \rightarrow \infty} \mathbf{d}_\kappa^i(s, t)$.

Proof. Let $\mathbf{d}_\kappa^\infty \in \mathcal{M}_\kappa(S)$ be given by $\mathbf{d}_\kappa^\infty(s, t) := \lim_{i \rightarrow \infty} \mathbf{d}_\kappa^i(s, t)$. We prove that $\mathbf{d}_\kappa^\infty = \mathbf{d}_\kappa$.

$\mathbf{d}_\kappa \preceq_\kappa \mathbf{d}_\kappa^\infty$: By $\mathbf{d}_\kappa \preceq_\kappa \mathbf{d}_\kappa^0$ and the monotonicity of \mathcal{F} , we can prove by induction on i that $\mathbf{d}_\kappa \preceq_\kappa \mathbf{d}_\kappa^i$ for all $i \in \mathbb{N}_0$. Thus $\mathbf{d}_\kappa \preceq_\kappa \mathbf{d}_\kappa^\infty$.

$\mathbf{d}_\kappa^\infty \preceq_\kappa \mathbf{d}_\kappa$: We prove that $\mathbf{d}_\kappa^\infty \preceq_\kappa \mathcal{F}_\kappa(\mathbf{d}_\kappa^\infty)$. Fix arbitrary $(s, t) \in S \times S$. Consider any $s \xrightarrow{a} \mu$. By Definition 12, for any $i \in \mathbb{N}$, there exists $t \xrightarrow{a} \nu_i$ such that $\Delta(\mathbf{d}_\kappa^i)(\mu, \nu_i) \leq \mathbf{d}_\kappa^{i+1}(s, t) \leq \mathbf{d}_\kappa^\infty(s, t)$. Since \mathcal{T} is finite, there exists $t \xrightarrow{a} \nu$ such that $\Delta(\mathbf{d}_\kappa^i)(\mu, \nu) \leq \mathbf{d}_\kappa^{i+1}(s, t) \leq \mathbf{d}_\kappa^\infty(s, t)$ for infinitely many $i \in \mathbb{N}$. Then since $\{\mathbf{d}_\kappa^i\}_{i \in \mathbb{N}_0}$ is decreasing w.r.t \preceq_κ and by Lemma 1, there exists $i \in \mathbb{N}$ such that for all $j \geq i$, $\Delta(\mathbf{d}_\kappa^j)(\mu, \nu) \leq \mathbf{d}_\kappa^\infty(s, t)$. Thus $\Delta(\mathbf{d}_\kappa^\infty)(\mu, \nu) \leq \mathbf{d}_\kappa^\infty(s, t)$ by Lemma 2. Similar arguments can be made for all $t \xrightarrow{a} \nu$. Thus $\mathbf{d}_\kappa^\infty \preceq_\kappa \mathcal{F}_\kappa(\mathbf{d}_\kappa^\infty)$.

Following Theorem 5 and the fact that $\mathbf{d}_d^0 = \mathbf{d}_p^0$, we have the following corollary:

Corollary 1. $\mathbf{d}_p = \mathbf{d}_d = \bigsqcup\{d \in \mathcal{M}_d(S) \mid d \preceq_d \mathcal{F}_d(d)\}$

This corollary allows us to reason properties of \mathbf{d}_p on $\mathcal{M}_d(S)$.

4 NP- and coNP-ness

In this section we study the complexity of the following problem:

- **Input:** a finite PA (S, Act, Ω) , $s_{\text{in}}, t_{\text{in}} \in S$ and a number $\epsilon \in \mathbb{Q}_{\geq 0}$ represented in binary
- **Output:** whether $\mathbf{d}_p(s_{\text{in}}, t_{\text{in}}) \leq \epsilon$ or not

More precisely, we consider the language

$$\mathcal{L} := \{\langle (S, \text{Act}, \Omega), \langle s_{\text{in}}, t_{\text{in}} \rangle, \epsilon \rangle \mid \mathbf{d}_p(s_{\text{in}}, t_{\text{in}}) \leq \epsilon\}$$

We prove that $\mathcal{L} \in \text{NP} \cap \text{coNP}$. Our proof method is divided into three steps: First we establish a characterization of the greatest fixed point \mathbf{d}_p (or equivalently \mathbf{d}_d since $\mathbf{d}_p = \mathbf{d}_d$); Then based on such characterization, we show that whether a given $d \in \mathcal{M}_p(S)$ equals \mathbf{d}_p is polynomial-time decidable; Finally, we complete the proof by showing how we can guess a pseudometric $d \in \mathcal{M}_p(S)$ which is also a fixed point of \mathcal{F}_p .

Below we fix a finite PA (S, Act, Ω) . First we present the characterization of the greatest fixed point \mathbf{d}_p . To this end we introduce the notion of “self-fulfilling” sets, as follows:

Definition 13. *Let $d \in \mathcal{M}_p(S)$ with $d = \mathcal{F}_p(d)$. A subset $X \subseteq S \times S$ is self-fulfilling w.r.t d iff for any $(s, t) \in X$, the following three conditions hold:*

1. $d(s, t) > 0$ (which implies that $s \neq t$) and $\text{Act}(s) = \text{Act}(t)$;
2. for any $s \xrightarrow{a} \mu$ such that $d(s, t) = \inf\{\Delta(d)(\mu, \nu) \mid t \xrightarrow{a} \nu\}$, there is $t \xrightarrow{a} \nu_0$ and $y = \{y_{s,t}\}_{s,t \in S} \in \text{OpS}(\Delta_d^{\mu, \nu_0})$ such that $d(s, t) = \Delta(d)(\mu, \nu_0)$ and $\lfloor y \rfloor \subseteq X$.
3. for any $t \xrightarrow{a} \nu$ such that $d(s, t) = \inf\{\Delta(d)(\mu, \nu) \mid s \xrightarrow{a} \mu\}$, there is $s \xrightarrow{a} \mu_0$ and $y = \{y_{s,t}\}_{s,t \in S} \in \text{OpS}(\Delta_d^{\mu_0, \nu})$ such that $d(s, t) = \Delta(d)(\mu_0, \nu)$ and $\lfloor y \rfloor \subseteq X$.

where $\lfloor y \rfloor := \{(s, t) \in S \times S \mid y_{s,t} > 0\}$.

Intuitively, a self-fulfilling set X w.r.t d is a set such that all values $d(s, t)$ of d in X can be reached on X itself. Below we show that nonempty self-fulfilling sets characterize exactly the greatest fixed point \mathbf{d}_p of the function \mathcal{F}_p .

Theorem 6. *Let $d \in \mathcal{M}_p(S)$ such that $d = \mathcal{F}_p(d)$. If $d \neq \mathbf{d}_p$, then there exists a nonempty self-fulfilling set $X \subseteq S \times S$ with respect to d .*

Proof. Suppose $d \neq \mathbf{d}_p$, we construct a nonempty self-fulfilling set X as described below. Denote $\delta(s, t) = d(s, t) - \mathbf{d}_p(s, t)$. Then $\delta(s, t) \geq 0$ for all $s, t \in S$, and there is $(s, t) \in S \times S$ such that $\delta(s, t) > 0$ due to $d \neq \mathbf{d}_p$. Define X to be the following set:

$$X := \{(s, t) \in S \times S \mid \delta(s, t) = \max\{\delta(s', t') \mid (s', t') \in S \times S\}\}$$

We prove that X is a nonempty self-fulfilling set. The non-emptiness of X is obvious. We further prove that any $(s, t) \in X$ satisfies the three conditions specified in Definition 13. Fix arbitrary $(s, t) \in X$. The analysis is as follows:

1. It is clear that $d(s, t) > 0$ since $\delta(s, t) > 0$. We prove that $\text{Act}(s) = \text{Act}(t)$. Suppose $\text{Act}(s) \neq \text{Act}(t)$. Then by Remark 2, $d(s, t) = \mathbf{d}_p(s, t) = 1$ which implies $\delta(s, t) = 0$. Contradiction. So (s, t) satisfies the first condition in Definition 13.
2. Suppose that $s \xrightarrow{a} \mu$ satisfies $d(s, t) = \inf\{\Delta(d)(\mu, \nu) \mid t \xrightarrow{a} \nu\}$ and $t \xrightarrow{a} \nu_0$ be arbitrarily chosen satisfying $\Delta(\mathbf{d}_p)(\mu, \nu_0) = \inf\{\Delta(\mathbf{d}_p)(\mu, \nu) \mid t \xrightarrow{a} \nu\}$. Choose an arbitrary $y = \{y_{s,t}\}_{s,t \in S} \in \text{OpS}(\Delta_d^{\mu, \nu_0})$. We prove that $y \in \text{OpS}(\Delta_d^{\mu, \nu_0})$ and $\lfloor y \rfloor \subseteq X$ (cf. Definition 13). By the definition of X , we have $\delta(s', t') \leq \delta(s, t)$ for all $(s', t') \in S \times S$. Thus for any $\{y_{s',t'}^*\}_{s',t' \in S} \in \text{Poly}(\Delta_d^{\mu, \nu_0})$, we have

$$\sum_{s', t' \in S} \mathbf{d}_p(s', t') \cdot y_{s',t'}^* \geq \sum_{s', t' \in S} (d(s', t') - \delta(s, t)) \cdot y_{s',t'}^* \quad (1)$$

Since $\sum_{s',t' \in S} y_{s',t'}^* = 1$, we can further simplify Inequality (1) as follows:

$$\sum_{s',t' \in S} \mathbf{d}_p(s',t') \cdot y_{s',t'}^* \geq \sum_{s',t' \in S} d(s',t') \cdot y_{s',t'}^* - \delta(s,t) \quad (2)$$

Note that $\text{Poly}(\Delta_d^{\mu,\nu_0}) = \text{Poly}(\Delta_{\mathbf{d}_p}^{\mu,\nu_0})$. So by taking the infimum at the both sides of Inequality 2, we obtain that $\Delta(\mathbf{d}_p)(\mu,\nu_0) \geq \Delta(d)(\mu,\nu_0) - \delta(s,t)$. Further from Definition 10, we obtain $\mathbf{d}_p(s,t) \geq \Delta(\mathbf{d}_p)(\mu,\nu_0)$. Thus, we have:

$$\mathbf{d}_p(s,t) \geq \Delta(\mathbf{d}_p)(\mu,\nu_0) \geq \Delta(d)(\mu,\nu_0) - \delta(s,t) \geq d(s,t) - \delta(s,t) = \mathbf{d}_p(s,t)$$

This means that $\mathbf{d}_p(s,t) = \Delta(\mathbf{d}_p)(\mu,\nu_0)$ and $d(s,t) = \Delta(d)(\mu,\nu_0)$. Then we can form another inequality series as follows:

$$\begin{aligned} & \sum_{s',t' \in S} d(s',t') \cdot y_{s',t'} \\ & \geq d(s,t) && \text{(by } d(s,t) = \Delta(d)(\mu,\nu_0)\text{)} \\ & = \mathbf{d}_p(s,t) + \delta(s,t) \\ & = \sum_{s',t' \in S} \mathbf{d}_p(s',t') \cdot y_{s',t'} + \delta(s,t) && \text{(by } \mathbf{d}_p(s,t) = \Delta(\mathbf{d}_p)(\mu,\nu_0)\text{)} \\ & = \sum_{s',t' \in S} (\mathbf{d}_p(s',t') + \delta(s,t)) \cdot y_{s',t'} \\ & \geq \sum_{s',t' \in S} (\mathbf{d}_p(s',t') + \delta(s',t')) \cdot y_{s',t'} \\ & = \sum_{s',t' \in S} d(s',t') \cdot y_{s',t'} \end{aligned}$$

Thus it must be the case that $y \in \text{OpS}(\Delta_d^{\mu,\nu_0})$ and $\delta(s',t') = \delta(s,t)$ whenever $y_{s',t'} > 0$. Then we have $[y] \subseteq X$. So (s,t) satisfies the second condition in Definition 13.

3. Symmetrically we can prove that (s,t) satisfies the third condition in Definition 13.

Hence in conclusion, X is a self-fulfilling set.

Theorem 7. *Let $d \in \mathcal{M}_p(S)$ such that $d = \mathcal{F}_p(d)$. If there exists a nonempty self-fulfilling set $X \subseteq S \times S$ with respect to d , then $d \neq \mathbf{d}_p$.*

Proof. Suppose $X \subseteq S \times S$ is a nonempty self-fulfilling set w.r.t d . We construct a distance function $d' \neq d$ such that $d' \preceq_d \mathcal{F}_d(d')$ and $d \preceq_d d'$. For all $(s \xrightarrow{a} \mu, t)$ and all $(s, t \xrightarrow{a} \nu)$ such that $(s,t) \in X$, we define the following differences: (note that $\text{Act}(s) = \text{Act}(t)$)

$$\begin{aligned} - & \delta[s \xrightarrow{a} \mu, t] := d(s,t) - \inf\{\Delta(d)(\mu,\nu') \mid t \xrightarrow{a} \nu'\}; \\ - & \delta[s, t \xrightarrow{a} \nu] := d(s,t) - \inf\{\Delta(d)(\mu',\nu) \mid s \xrightarrow{a} \mu'\}. \end{aligned}$$

All the differences defined above are non-negative since $d = \mathcal{F}_p(d)$. Further we define the following two differences: (where $\min \emptyset := 0$)

$$\begin{aligned} - & \delta_1 := \min\{\delta[s \xrightarrow{a} \mu, t] \mid (s,t) \in X, s \xrightarrow{a} \mu \text{ and } \delta[s \xrightarrow{a} \mu, t] > 0\}; \\ - & \delta_2 := \min\{\delta[s, t \xrightarrow{a} \nu] \mid (s,t) \in X, t \xrightarrow{a} \nu \text{ and } \delta[s, t \xrightarrow{a} \nu] > 0\}. \end{aligned}$$

Finally we define the difference value δ as follows:

$$\delta := \begin{cases} \min\{\delta_1, \delta_2, \min\{d(s,t) \mid (s,t) \in X\}\} & \text{if } \delta_1 \neq 0 \text{ and } \delta_2 \neq 0 \\ \min\{\delta_2, \min\{d(s,t) \mid (s,t) \in X\}\} & \text{if } \delta_1 = 0 \text{ and } \delta_2 \neq 0 \\ \min\{\delta_1, \min\{d(s,t) \mid (s,t) \in X\}\} & \text{if } \delta_1 \neq 0 \text{ and } \delta_2 = 0 \\ \min\{d(s,t) \mid (s,t) \in X\} & \text{if } \delta_1 = 0 \text{ and } \delta_2 = 0 \end{cases}$$

Note that $\delta > 0$. Then we construct $d' \in \mathcal{M}_d(S)$ by:

$$d'(s, t) := \begin{cases} d(s, t) - \frac{1}{2}\delta & \text{if } (s, t) \in X \\ d(s, t) & \text{if } (s, t) \notin X \end{cases}$$

It is clear that $d' \neq d$ since X is non-empty. We prove that $d' \preceq_d \mathcal{F}_d(d')$. Fix an arbitrary $(s, t) \in S \times S$. Suppose $(s, t) \notin X$. Then from $d \preceq_d d'$ we have $\mathcal{F}_d(d) \preceq_d \mathcal{F}_d(d')$. And then we have $d'(s, t) = d(s, t) = \mathcal{F}_p(d)(s, t) = \mathcal{F}_d(d)(s, t) \geq \mathcal{F}_d(d')(s, t)$. Thus $d'(s, t) \geq \mathcal{F}_d(d')(s, t)$. Suppose now that $(s, t) \in X$. For any $s \xrightarrow{a} \mu$, we clarify two cases below:

Case 1: $\delta[s \xrightarrow{a} \mu, t] > 0$. Then $\delta_1 > 0$. By definition, we have:

$$d'(s, t) \geq d(s, t) - \frac{1}{2}\delta > d(s, t) - \delta[s \xrightarrow{a} \mu, t] = \inf\{\Delta(d)(\mu, \nu') \mid t \xrightarrow{a} \nu'\}$$

From $d \preceq_d d'$, we have $\inf\{\Delta(d)(\mu, \nu') \mid t \xrightarrow{a} \nu'\} \geq \inf\{\Delta(d')(\mu, \nu') \mid t \xrightarrow{a} \nu'\}$. Thus $d'(s, t) \geq \inf\{\Delta(d')(\mu, \nu') \mid t \xrightarrow{a} \nu'\}$.

Case 2: $\delta[s \xrightarrow{a} \mu, t] = 0$. Then since X is self-fulfilling there is $t \xrightarrow{a} \nu_0$ and $y = \{y_{s', t'}\}_{s', t' \in S} \in \text{OpS}(\Delta_d^{\mu, \nu_0})$ such that $d(s, t) = \Delta(d)(\mu, \nu_0)$ and $\lfloor y \rfloor \subseteq X$. From $\lfloor y \rfloor \subseteq X$ we obtain

$$\sum_{s', t' \in S} d'(s', t') \cdot y_{s', t'} = \sum_{s', t' \in S} d(s', t') \cdot y_{s', t'} - \frac{1}{2}\delta = \Delta(d)(\mu, \nu_0) - \frac{1}{2}\delta = d'(s, t)$$

Then we have: $\inf\{\Delta(d')(\mu, \nu') \mid t \xrightarrow{a} \nu'\} \leq \Delta(d')(\mu, \nu_0) \leq \sum_{s', t' \in S} d'(s', t') \cdot y_{s', t'} = d'(s, t)$. Thus $d'(s, t) \geq \inf\{\Delta(d')(\mu, \nu') \mid t \xrightarrow{a} \nu'\}$ for all $s \xrightarrow{a} \mu$. Similarly we can prove that $d'(s, t) \geq \inf\{\Delta(d')(\mu', \nu) \mid s \xrightarrow{a} \mu'\}$ for all $t \xrightarrow{a} \nu$. Thus $d'(s, t) \geq \mathcal{F}_d(d')(s, t)$ for all $(s, t) \in S \times S$. Hence $d' \preceq_d \mathcal{F}_d(d')$. By $d \preceq_d d'$ we have $d \neq \bigsqcup\{\mathfrak{d} \in \mathcal{M}_d(S) \mid \mathfrak{d} \preceq_d \mathcal{F}_d(\mathfrak{d})\}$. Then by Corollary 1, we obtain that $d \neq \mathbf{d}_p$.

Thus for any $d \in \mathcal{M}_p(S)$ satisfying $d = \mathcal{F}_p(d)$, $d \neq \mathbf{d}_p$ iff there exists a nonempty self-fulfilling set w.r.t d . This characterization means that to check whether $d \neq \mathbf{d}_p$ or not, we can equivalently check whether there exists a nonempty self-fulfilling set or not. The intuition here is that for any self-fulfilling sets X, Y , $X \cup Y$ is still a self-fulfilling set; thus there exists a largest self-fulfilling set. This gives rise to a refinement algorithm that computes the largest self-fulfilling set.

Theorem 8. Denote $\text{FP} := \{d \in \mathcal{M}_p(S) \mid d = \mathcal{F}_p(d)\}$ to be the set of fixed points of \mathcal{F}_p . The problem whether a given $d \in \text{FP}$ equals \mathbf{d}_p is decidable in polynomial time.

Proof. From Theorem 6 and Theorem 7, we can solve the problem by checking whether there exists a nonempty self-fulfilling set w.r.t the given $d \in \text{FP}$. Note that for any self-fulfilling sets X, Y w.r.t d , $X \cup Y$ is still self-fulfilling w.r.t d . So there exists a largest self-fulfilling set w.r.t d , which is denoted as Z . Then there exists a nonempty self-fulfilling set w.r.t d iff Z is nonempty. Below we develop a refinement algorithm to compute Z .

First we define a refinement function $\text{ref} : \mathcal{E} \rightarrow \mathcal{E}$, where the set \mathcal{E} is given as follows:

$$\mathcal{E} := \{X \subseteq S \times S \mid \text{Act}(s) = \text{Act}(t) \text{ and } d(s, t) > 0 \text{ for all } (s, t) \in X\}$$

Note that \mathcal{E} is nonempty since $\emptyset \in \mathcal{E}$. Given $X \in \mathcal{E}$, we define $\delta_X := \min\{d(s, t) \mid (s, t) \in X\}$ (where $\min \emptyset = 0$) and the distance function $d_X \in \mathcal{M}_d(S)$ as follows:

$$d_X(s, t) = \begin{cases} d(s, t) - \delta_X & \text{if } (s, t) \in X \\ d(s, t) & \text{if } (s, t) \notin X \end{cases}$$

Then the set $ref(X) \in \mathcal{E}$ is defined as follows: $(s, t) \in ref(X)$ iff $(s, t) \in X$ and further (s, t) satisfies the following two conditions:

1. for all $s \xrightarrow{a} \mu$, if $d(s, t) = \inf\{\Delta(d)(\mu, \nu) \mid t \xrightarrow{a} \nu\}$ then:

$$d_X(s, t) \geq \inf\{\Delta(d_X)(\mu, \nu) \mid t \xrightarrow{a} \nu\}$$
2. for all $t \xrightarrow{a} \nu$, if $d(s, t) = \inf\{\Delta(d)(\mu, \nu) \mid s \xrightarrow{a} \mu\}$ then:

$$d_X(s, t) \geq \inf\{\Delta(d_X)(\mu, \nu) \mid s \xrightarrow{a} \mu\}$$

Note that $ref(X) \subseteq X$ for all $X \in \mathcal{E}$. Now we construct a sequence $\{Z_i\}_{i \in \mathbb{N}_0}$ as follows:

$$Z_0 = \{(s, t) \in S \times S \mid \text{Act}(s) = \text{Act}(t) \text{ and } d(s, t) > 0\}; Z_{i+1} = ref(Z_i)$$

By $Z_{i+1} \subseteq Z_i$, there exists $n \leq |Z_0|$ such that $Z_{n+1} = ref(Z_n) = Z_n$. We show that $Z_n = Z$.

“ $Z \subseteq Z_n$ ”: We prove by induction that $Z \subseteq Z_i$ for all $i \in \mathbb{N}_0$. The base step $Z \subseteq Z_0$ is clear from the definition. For inductive step, suppose that $Z \subseteq Z_i$. We show that $Z \subseteq Z_{i+1}(= ref(Z_i))$. Fix arbitrary $(s, t) \in Z$. Consider any $s \xrightarrow{a} \mu$ such that $d(s, t) = \inf\{\Delta(d)(\mu, \nu) \mid t \xrightarrow{a} \nu\}$. Since Z is self-fulfilling, there is $t \xrightarrow{a} \nu_0$ and $y = \{y_{s', t'}\}_{s', t' \in S} \in \text{OpS}(\Delta_d^{\mu, \nu_0})$ such that $d(s, t) = \Delta(d)(\mu, \nu_0)$ and $[y] \subseteq Z$. Since $Z \subseteq Z_i$, we have $d_{Z_i}(s, t) = d(s, t) - \delta_{Z_i}$ and $d_{Z_i}(s', t') = d(s', t') - \delta_{Z_i}$ for all $(s', t') \in [y]$. Thus we obtain

$$\sum_{s', t' \in S} d_{Z_i}(s', t') \cdot y_{s', t'} = \sum_{s', t' \in S} (d(s', t') - \delta_{Z_i}) \cdot y_{s', t'} = d(s, t) - \delta_{Z_i} = d_{Z_i}(s, t)$$

Hence $d_{Z_i}(s, t) \geq \Delta(d_{Z_i})(\mu, \nu_0) \geq \inf\{\Delta(d_{Z_i})(\mu, \nu) \mid t \xrightarrow{a} \nu\}$. By a similar reasoning we can prove that for all $t \xrightarrow{a} \nu$, if $d(s, t) = \inf\{\Delta(d)(\mu, \nu) \mid s \xrightarrow{a} \mu\}$ then $d_{Z_i}(s, t) \geq \inf\{\Delta(d_{Z_i})(\mu, \nu) \mid s \xrightarrow{a} \mu\}$. So $(s, t) \in Z_{i+1}$. Thus $Z \subseteq Z_{i+1}$.

“ $Z_n \subseteq Z$ ”: We prove that Z_n is a self-fulfilling set, i.e., Z_n satisfies the three conditions specified in Definition 13. W.l.o.g we can assume that $Z_n \neq \emptyset$. The first condition in Definition 13 is directly satisfied since $Z_n \subseteq Z_0$. As for the second condition, consider any $(s, t) \in Z_n$ and $s \xrightarrow{a} \mu$ satisfying $d(s, t) = \inf\{\Delta(d)(\mu, \nu) \mid t \xrightarrow{a} \nu\}$. By $Z_n = ref(Z_n)$, $d_{Z_n}(s, t) \geq \inf\{\Delta(d_{Z_n})(\mu, \nu) \mid t \xrightarrow{a} \nu\}$. Choose $t \xrightarrow{a} \nu_0$ such that $\Delta(d_{Z_n})(\mu, \nu_0) = \inf\{\Delta(d_{Z_n})(\mu, \nu) \mid t \xrightarrow{a} \nu\}$ and an arbitrary $y \in \text{OpS}(\Delta_{d_{Z_n}}^{\mu, \nu_0})$. Then since $d_{Z_n}(s, t) = d(s, t) - \delta_{Z_n}$, we have

$$\begin{aligned} d(s, t) &\geq \Delta(d_{Z_n})(\mu, \nu_0) + \delta_{Z_n} \\ &= \sum_{s', t' \in S} (d_{Z_n}(s', t') + \delta_{Z_n}) \cdot y_{s', t'} \\ &\geq \sum_{s', t' \in S} d(s', t') \cdot y_{s', t'} \\ &\geq \Delta(d)(\mu, \nu_0) \\ &\geq d(s, t) \end{aligned}$$

Thus $d(s, t) = \Delta(d)(\mu, \nu_0)$, $y \in \text{OpS}(\Delta_d^{\mu, \nu_0})$ and $d_{Z_n}(s', t') = d(s', t') - \delta_{Z_n}$ for all $(s', t') \in [y]$, which implies that $[y] \subseteq Z_n$ since $\delta_{Z_n} > 0$. Then the result follows.

The reasoning for the third condition can be carried out in the same way as for the second condition.

Thus to compute Z , we need only to apply ref to Z_0 at most $|Z_0|$ times. Note that the computation of ref can be carried out in polynomial time since the optimal value of a linear programming problem can be computed in polynomial time. Hence Z is polynomial-time computable. Then it follows directly that whether a given $d \in \text{FP}$ equals \mathbf{d}_p is decidable in polynomial time.

By Theorem 8, we can decide if a given element in FP is \mathbf{d}_p in polynomial time. However, it does not tell us how to obtain an element in FP . Below we show that we can guess such an element using only polynomial random-bits. This is also the final step to prove that $\mathcal{L} \in \text{NP} \cap \text{coNP}$. (see the beginning of the section for the definition of \mathcal{L})

Theorem 9. $\mathcal{L} \in \text{NP} \cap \text{coNP}$.

Proof. We only show that $\mathcal{L}^c \in \text{NP}$, since proving $\mathcal{L} \in \text{NP}$ is similar. W.l.o.g we assume that $\mathcal{L}^c := \{ \langle \langle S, \text{Act}, \Omega \rangle, \langle s_{\text{in}}, t_{\text{in}} \rangle, \epsilon \rangle \mid \mathbf{d}_p(s_{\text{in}}, t_{\text{in}}) > \epsilon \}$. Let (S, Act, Ω) , $(s_{\text{in}}, t_{\text{in}})$ and ϵ be the input. Our strategy to obtain a NP algorithm for \mathcal{L}^c is as follows:

1. We guess a $d \in \text{FP}$ by using Theorem 2 and Theorem 1.
2. We check whether $d = \mathbf{d}_p$ by Theorem 8; if $d = \mathbf{d}_p$ then we check whether $d(s, t) > \epsilon$, otherwise we fail.

Below we show that how we can guess a $d \in \text{FP}$ using only polynomial bits. The guessing procedure is illustrated step by step as follows.

1. For all $s \xrightarrow{a} \mu$ and $t \in S$ such that $\text{Act}(s) = \text{Act}(t) \neq \emptyset$, we guess a $\nu[s \xrightarrow{a} \mu, t]$ such that $t \xrightarrow{a} \nu[s \xrightarrow{a} \mu, t]$. Then we guess $|S|^2$ constraints (informally “rows”) specified in the LP $\Delta_{\mathfrak{D}}^{\mu, \nu[s \xrightarrow{a} \mu, t]}$ (cf. Tab. 1). Note that the parameter \mathfrak{D} is irrelevant here. We denote the guessed collection of constraints (w.r.t $s \xrightarrow{a} \mu$ and t) as $\{h_i^T y \text{ op}_i b^i\}_{i \in I[s \xrightarrow{a} \mu, t]}$, where
 - $y = \{y_{s', t'}\}_{s', t' \in S}$ represents the variable vector;
 - $I[s \xrightarrow{a} \mu, t]$ is the set of indexes of the guessed rows;
 - $h_i^T y \text{ op}_i b^i$ is the constraint at the i -th row, for which $\text{op}_i \in \{\leq, \geq, =\}$ is the comparison operator at the i -th row.

We check in polynomial time whether for all $s \xrightarrow{a} \mu$ and $t \in S$, the linear equation system $\{h_i^T y = b^i\}_{i \in I[s \xrightarrow{a} \mu, t]}$ has a unique solution (through, e.g., Gaussian Elimination). We fail if the checking result is negative; Otherwise we denote the unique solution to be $y[s \xrightarrow{a} \mu, t]$ (a vector over $S \times S$), and proceed to the next step.

2. For all $t \xrightarrow{a} \nu$ and $s \in S$ such that $\text{Act}(s) = \text{Act}(t) \neq \emptyset$, we perform similar guessings illustrated in Step 1. We guess a $\mu[s, t \xrightarrow{a} \nu]$, and further $|S|^2$ constraints specified in the LP $\Delta_{\mathfrak{D}}^{\mu[s, t \xrightarrow{a} \nu], \nu}$. We denote the guessed constraints as $\{h_i^T y \text{ op}_i b^i\}_{i \in I[s, t \xrightarrow{a} \nu]}$. Then we check whether for all $t \xrightarrow{a} \nu$ and $s \in S$, the linear equation system $\{h_i^T y = b^i\}_{i \in I[s, t \xrightarrow{a} \nu]}$ has a unique solution. We fail if the checking result is negative; Otherwise we denote the unique solution as $y[s, t \xrightarrow{a} \nu]$, and proceed to the next step.

3. We compute a distance function $d \in \mathcal{M}_d(S)$ defined by: $d(s, t) = \text{OpV}(\Gamma_{s,t})$ for all $s, t \in S$, where the LP $\Gamma_{s,t}$ (with variables $\{z_{s',t'}\}_{s',t' \in S}$) is specified by:

minimize $z_{s,t}$
subject to:

- (i) $z_{s',s'} = 0$, $z_{s',t'} = z_{t',s'}$ and $z_{r',t'} \leq z_{r',s'} + z_{s',t'}$ for all $r', s', t' \in S$
- (ii) $0 \leq z_{s',t'} \leq 1$ for all $s', t' \in S$
- (iii) $z_{s',t'} \geq \sum_{\mathfrak{s}, \mathfrak{t} \in S} (y[s' \xrightarrow{a} \mu, t'])_{\mathfrak{s}, \mathfrak{t}} \cdot z_{\mathfrak{s}, \mathfrak{t}}$ for all $t' \in S$ and all $s' \xrightarrow{a} \mu$ such that $\text{Act}(s') = \text{Act}(t') \neq \emptyset$
- (iv) $z_{s',t'} \geq \sum_{\mathfrak{s}, \mathfrak{t} \in S} (y[s', t' \xrightarrow{a} \nu])_{\mathfrak{s}, \mathfrak{t}} \cdot z_{\mathfrak{s}, \mathfrak{t}}$ for all $s' \in S$ and all $t' \xrightarrow{a} \nu$ such that $\text{Act}(s') = \text{Act}(t') \neq \emptyset$
- (v) $z_{s',t'} = 0$ for all $s', t' \in S$ such that $\text{Act}(s') = \text{Act}(t') = \emptyset$.
- (vi) $z_{s',t'} = 1$ for all $s', t' \in S$ such that $\text{Act}(s') \neq \text{Act}(t')$.

If there is $\Gamma_{s,t}$ that has no feasible solution (which can also be decided in polynomial time), we fail; Otherwise we proceed to the next step.

4. We check whether $d \in \mathcal{M}_p(S)$ and $d = \mathcal{F}_p(d)$, which can be done in polynomial time. We fail if the checking is unsuccessful; otherwise we have guessed a $d \in \text{FP}$.

Then (as is previously mentioned), the final step is to check whether $d = \mathbf{d}_p$: if $d = \mathbf{d}_p$ then we return the comparison result of $d(s, t) > \epsilon$; otherwise we fail. It is clear that if we can guess a $d \in \text{FP}$ and check successfully that $d = \mathbf{d}_p$, then the returned result is surely correct. Below we prove that \mathbf{d}_p can be guessed through the guessing procedure.

Consider Step 1. For any $s \xrightarrow{a} \mu$ and $t \in S$ such that $\text{Act}(s) = \text{Act}(t) \neq \emptyset$, we choose $\nu[s \xrightarrow{a} \mu, t]$ such that $\Delta(\mathbf{d}_p)(\mu, \nu[s \xrightarrow{a} \mu, t]) = \inf\{\Delta(\mathbf{d}_p)(\mu, \nu) \mid t \xrightarrow{a} \nu\}$. By Theorem 2, we can choose $y[s \xrightarrow{a} \mu, t]$ to be a vertex of $\Delta_{\mathfrak{D}}^{\mu, \nu[s \xrightarrow{a} \mu, t]}$ that reaches $\text{OpV}(\Delta_{\mathfrak{D}}^{\mu, \nu[s \xrightarrow{a} \mu, t]})$. Then by Theorem 1, we choose constraints $\{h_i^T y \text{ op}_i b^i\}_{i \in I[s \xrightarrow{a} \mu, t]}$ such that $\{h_i^T\}_{i \in I[s \xrightarrow{a} \mu, t]}$ are exactly the row vectors of the matrix $A_{y[s \xrightarrow{a} \mu, t]}$ (cf. Theorem 1). Here by Remark 1, we can abuse Theorem 1 on constraints like “ $h^T y \geq e$ ” and “ $h^T y = e$ ”. Then surely the unique solution of $\{h_i^T y = b^i\}_{i \in I[s \xrightarrow{a} \mu, t]}$ is $y[s \xrightarrow{a} \mu, t]$. Similarly, we choose $y[s, t \xrightarrow{a} \nu]$ for all $s \in S$ and $t \xrightarrow{a} \nu$ such that $\text{Act}(s) = \text{Act}(t) \neq \emptyset$ in Step 2.

Then consider Step 3. We show that the $d \in \mathcal{M}_d(S)$ defined in Step 3 is equal to \mathbf{d}_p , provided that $y[s' \xrightarrow{a} \mu, t']$ and $y[s', t' \xrightarrow{a} \nu]$ are chosen as above.

1. $\mathbf{d}_p \preceq_d d$: By the definition of pseudometrics and Remark 2, the vector $\{z_{s',t'}^*\}_{s',t' \in S}$ is a feasible solution of $\Gamma_{s,t}$ for all $s, t \in S$, where $\{z_{s',t'}^*\}_{s',t' \in S}$ is given by: $z_{s',t'}^* = \mathbf{d}_p(s', t')$ for all $s', t' \in S$. Thus immediately we have $\mathbf{d}_p \preceq_d d$.
2. $d \preceq_d \mathbf{d}_p$: Fix arbitrary $(s, t) \in S \times S$ and let $\{\mathbf{z}_{s',t'}\}_{s',t' \in S}$ be an optimal solution of $\Gamma_{s,t}$. Define $d' \in \mathcal{M}_d(S)$ by: $d'(s', t') = \mathbf{z}_{s',t'}$ for arbitrary $s', t' \in S$. Then for any $t' \in S$ and $s' \xrightarrow{a} \mu$ such that $\text{Act}(s') = \text{Act}(t') \neq \emptyset$,

$$d'(s', t') \geq \sum_{\mathfrak{s}, \mathfrak{t} \in S} (y[s' \xrightarrow{a} \mu, t'])_{\mathfrak{s}, \mathfrak{t}} \cdot d'(\mathfrak{s}, \mathfrak{t}) \geq \Delta(d')(\mu, \nu[s' \xrightarrow{a} \mu, t'])$$

Hence $d'(s', t') \geq \inf\{\Delta(d')(\mu, \nu) \mid t' \xrightarrow{a} \nu\}$. In a similar way, we can prove that $d'(s', t') \geq \inf\{\Delta(d')(\mu, \nu) \mid s' \xrightarrow{a} \mu\}$ for all $s' \in S$ and $t' \xrightarrow{a} \nu$ such

that $\text{Act}(s') = \text{Act}(t') \neq \emptyset$. Thus $d' \preceq_d \mathcal{F}_d(d')$ and hence $d' \preceq_d \mathbf{d}_p$. Then $d(s, t) \geq \mathbf{d}_p(s, t)$ since $d(s, t) = d'(s, t)$.

In conclusion, \mathbf{d}_p can be obtained on certain random bits in the guessing procedure.

5 Conclusion and Future Work

We have shown that the problem whether the distance between two given states of a finite simple probabilistic automata under a non-future-discounting pseudometric derived from a real-valued logic lies in $\text{NP} \cap \text{coNP}$, which significantly improves previous PSPACE upperbound [vBSW07,CHL09]. We prove this by establishing the original notion of “self-fulfilling” sets, and then exploring the relationship between our pseudometric and self-fulfilling sets. Our future work is to investigate if the problem further lies in PTIME, and whether there is an efficient error-tolerant algorithm for this problem. It is also possible to extend the result of this paper to game metrics [dAMRS07].

References

- [ASB95] Adnan Aziz, Vigyan Singhal, and Felice Balarin. It usually works: The temporal logic of stochastic systems. In *CAV*, pages 155–165, 1995.
- [BEMC00] Christel Baier, Bettina Engelen, and Mila E. Majster-Cederbaum. Deciding bisimilarity and similarity for probabilistic processes. *J. Comput. Syst. Sci.*, 60(1):187–231, 2000.
- [CHL09] Taolue Chen, Tingting Han, and Jian Lu. On metrics for probabilistic systems: Definitions and algorithms. *Computers & Mathematics with Applications*, 57(6):991–999, 2009.
- [CS02] Stefano Cattani and Roberto Segala. Decision algorithms for probabilistic bisimulation. In *CONCUR*, pages 371–385, 2002.
- [dAMRS07] Luca de Alfaro, Rupak Majumdar, Vishwanath Raman, and Mariëlle Stoelinga. Game relations and metrics. In *LICS*, pages 99–108, 2007.
- [DGJP04] Josee Desharnais, Vineet Gupta, Radha Jagadeesan, and Prakash Panangaden. Metrics for labelled markov processes. *Theor. Comput. Sci.*, 318(3):323–354, 2004.
- [GcJS90] Alessandro Giacalone, Chi chang Jou, and Scott A. Smolka. Algebraic reasoning for probabilistic concurrent systems. In *Proc. IFIP TC2 Working Conference on Programming Concepts and Methods*, pages 443–458. North-Holland, 1990.
- [JL91] Bengt Jonsson and Kim Guldstrand Larsen. Specification and refinement of probabilistic processes. In *LICS*, pages 266–277, 1991.
- [Kan42] L. Kantorovich. On the transfer of masses (in Russian). *Doklady Akademii Nauk*, 37(2):227–229, 1942. Translated in *Management Science*, 5:1-4, 1959.
- [KR58] L.V. Kantorovich and G.Sh. Rubinstein. On the space of completely additive functions. *Vestnik Leningradskogo Universiteta*, 3(2):52–59, 1958. In Russian.
- [LS91] Kim Guldstrand Larsen and Arne Skou. Bisimulation through probabilistic testing. *Inf. Comput.*, 94(1):1–28, 1991.
- [Pan09] Prakash Panangaden. *Labelled Markov Processes*. Imperial College Press, 2009.
- [Sch10] Alexander Schrijver. *A Course in Combinatorial Optimization*. Course notes, available at <http://homepages.cwi.nl/~lex/>, 2010.
- [SL95] Roberto Segala and Nancy A. Lynch. Probabilistic simulations for probabilistic processes. *Nord. J. Comput.*, 2(2):250–273, 1995.
- [vBSW07] Franck van Breugel, Babita Sharma, and James Worrell. Approximating a behavioural pseudometric without discount for probabilistic systems. In *FoSSaCS*, pages 123–137, 2007.
- [vBW01a] Franck van Breugel and James Worrell. An algorithm for quantitative verification of probabilistic transition systems. In *CONCUR*, pages 336–350, 2001.
- [vBW01b] Franck van Breugel and James Worrell. Towards quantitative verification of probabilistic transition systems. In *ICALP*, pages 421–432, 2001.

Aachener Informatik-Berichte

This is the list of all technical reports since 1987. To obtain copies of reports please consult

<http://aib.informatik.rwth-aachen.de/>

or send your request to:

Informatik-Bibliothek, RWTH Aachen, Ahornstr. 55, 52056 Aachen,
Email: biblio@informatik.rwth-aachen.de

- 1987-01 * Fachgruppe Informatik: Jahresbericht 1986
- 1987-02 * David de Frutos Escrig, Klaus Indermark: Equivalence Relations of Non-Deterministic Ianov-Schemes
- 1987-03 * Manfred Nagl: A Software Development Environment based on Graph Technology
- 1987-04 * Claus Lewerentz, Manfred Nagl, Bernhard Westfechtel: On Integration Mechanisms within a Graph-Based Software Development Environment
- 1987-05 * Reinhard Rinn: Über Eingabeanomalien bei verschiedenen Inferenzmodellen
- 1987-06 * Werner Damm, Gert Döhmen: Specifying Distributed Computer Architectures in AADL*
- 1987-07 * Gregor Engels, Claus Lewerentz, Wilhelm Schäfer: Graph Grammar Engineering: A Software Specification Method
- 1987-08 * Manfred Nagl: Set Theoretic Approaches to Graph Grammars
- 1987-09 * Claus Lewerentz, Andreas Schürr: Experiences with a Database System for Software Documents
- 1987-10 * Herbert Klaeren, Klaus Indermark: A New Implementation Technique for Recursive Function Definitions
- 1987-11 * Rita Loogen: Design of a Parallel Programmable Graph Reduction Machine with Distributed Memory
- 1987-12 J. Börstler, U. Möncke, R. Wilhelm: Table compression for tree automata
- 1988-01 * Gabriele Esser, Johannes Rückert, Frank Wagner Gesellschaftliche Aspekte der Informatik
- 1988-02 * Peter Martini, Otto Spaniol: Token-Passing in High-Speed Backbone Networks for Campus-Wide Environments
- 1988-03 * Thomas Welzel: Simulation of a Multiple Token Ring Backbone
- 1988-04 * Peter Martini: Performance Comparison for HSLAN Media Access Protocols
- 1988-05 * Peter Martini: Performance Analysis of Multiple Token Rings
- 1988-06 * Andreas Mann, Johannes Rückert, Otto Spaniol: Datenfunknetze
- 1988-07 * Andreas Mann, Johannes Rückert: Packet Radio Networks for Data Exchange
- 1988-08 * Andreas Mann, Johannes Rückert: Concurrent Slot Assignment Protocol for Packet Radio Networks
- 1988-09 * W. Kremer, F. Reichert, J. Rückert, A. Mann: Entwurf einer Netzwerktopologie für ein Mobilfunknetz zur Unterstützung des öffentlichen Straßenverkehrs

- 1988-10 * Kai Jakobs: Towards User-Friendly Networking
- 1988-11 * Kai Jakobs: The Directory - Evolution of a Standard
- 1988-12 * Kai Jakobs: Directory Services in Distributed Systems - A Survey
- 1988-13 * Martine Schümmer: RS-511, a Protocol for the Plant Floor
- 1988-14 * U. Quernheim: Satellite Communication Protocols - A Performance Comparison Considering On-Board Processing
- 1988-15 * Peter Martini, Otto Spaniol, Thomas Welzel: File Transfer in High Speed Token Ring Networks: Performance Evaluation by Approximate Analysis and Simulation
- 1988-16 * Fachgruppe Informatik: Jahresbericht 1987
- 1988-17 * Wolfgang Thomas: Automata on Infinite Objects
- 1988-18 * Michael Sonnenschein: On Petri Nets and Data Flow Graphs
- 1988-19 * Heiko Vogler: Functional Distribution of the Contextual Analysis in Block-Structured Programming Languages: A Case Study of Tree Transducers
- 1988-20 * Thomas Welzel: Einsatz des Simulationswerkzeuges QNAP2 zur Leistungsbewertung von Kommunikationsprotokollen
- 1988-21 * Th. Janning, C. Lewerentz: Integrated Project Team Management in a Software Development Environment
- 1988-22 * Joost Engelfriet, Heiko Vogler: Modular Tree Transducers
- 1988-23 * Wolfgang Thomas: Automata and Quantifier Hierarchies
- 1988-24 * Uschi Heuter: Generalized Definite Tree Languages
- 1989-01 * Fachgruppe Informatik: Jahresbericht 1988
- 1989-02 * G. Esser, J. Rückert, F. Wagner (Hrsg.): Gesellschaftliche Aspekte der Informatik
- 1989-03 * Heiko Vogler: Bottom-Up Computation of Primitive Recursive Tree Functions
- 1989-04 * Andy Schürr: Introduction to PROGRESS, an Attribute Graph Grammar Based Specification Language
- 1989-05 J. Börstler: Reuse and Software Development - Problems, Solutions, and Bibliography (in German)
- 1989-06 * Kai Jakobs: OSI - An Appropriate Basis for Group Communication?
- 1989-07 * Kai Jakobs: ISO's Directory Proposal - Evolution, Current Status and Future Problems
- 1989-08 * Bernhard Westfechtel: Extension of a Graph Storage for Software Documents with Primitives for Undo/Redo and Revision Control
- 1989-09 * Peter Martini: High Speed Local Area Networks - A Tutorial
- 1989-10 * P. Davids, Th. Welzel: Performance Analysis of DQDB Based on Simulation
- 1989-11 * Manfred Nagl (Ed.): Abstracts of Talks presented at the WG '89 15th International Workshop on Graphtheoretic Concepts in Computer Science
- 1989-12 * Peter Martini: The DQDB Protocol - Is it Playing the Game?
- 1989-13 * Martine Schümmer: CNC/DNC Communication with MAP
- 1989-14 * Martine Schümmer: Local Area Networks for Manufacturing Environments with hard Real-Time Requirements

- 1989-15 * M. Schümmer, Th. Welzel, P. Martini: Integration of Field Bus and MAP Networks - Hierarchical Communication Systems in Production Environments
- 1989-16 * G. Vossen, K.-U. Witt: SUXESS: Towards a Sound Unification of Extensions of the Relational Data Model
- 1989-17 * J. Derissen, P. Hruschka, M.v.d. Beeck, Th. Janning, M. Nagl: Integrating Structured Analysis and Information Modelling
- 1989-18 A. Maassen: Programming with Higher Order Functions
- 1989-19 * Mario Rodriguez-Artalejo, Heiko Vogler: A Narrowing Machine for Syntax Directed BABEL
- 1989-20 H. Kuchen, R. Loogen, J.J. Moreno Navarro, M. Rodriguez Artalejo: Graph-based Implementation of a Functional Logic Language
- 1990-01 * Fachgruppe Informatik: Jahresbericht 1989
- 1990-02 * Vera Jansen, Andreas Potthoff, Wolfgang Thomas, Udo Wermuth: A Short Guide to the AMORE System (Computing Automata, MONoids and Regular Expressions)
- 1990-03 * Jerzy Skurczynski: On Three Hierarchies of Weak SkS Formulas
- 1990-04 R. Loogen: Stack-based Implementation of Narrowing
- 1990-05 H. Kuchen, A. Wagener: Comparison of Dynamic Load Balancing Strategies
- 1990-06 * Kai Jakobs, Frank Reichert: Directory Services for Mobile Communication
- 1990-07 * Kai Jakobs: What's Beyond the Interface - OSI Networks to Support Cooperative Work
- 1990-08 * Kai Jakobs: Directory Names and Schema - An Evaluation
- 1990-09 * Ulrich Quernheim, Dieter Kreuer: Das CCITT - Signalisierungssystem Nr. 7 auf Satellitenstrecken; Simulation der Zeichengabestrecke
- 1990-11 H. Kuchen, R. Loogen, J.J. Moreno Navarro, M. Rodriguez Artalejo: Lazy Narrowing in a Graph Machine
- 1990-12 * Kai Jakobs, Josef Kaltwasser, Frank Reichert, Otto Spaniol: Der Computer fährt mit
- 1990-13 * Rudolf Mathar, Andreas Mann: Analyzing a Distributed Slot Assignment Protocol by Markov Chains
- 1990-14 A. Maassen: Compilerentwicklung in Miranda - ein Praktikum in funktionaler Programmierung (written in german)
- 1990-15 * Manfred Nagl, Andreas Schürr: A Specification Environment for Graph Grammars
- 1990-16 A. Schürr: PROGRESS: A VHL-Language Based on Graph Grammars
- 1990-17 * Marita Möller: Ein Ebenenmodell wissensbasierter Konsultationen - Unterstützung für Wissensakquisition und Erklärungsfähigkeit
- 1990-18 * Eric Kowalewski: Entwurf und Interpretation einer Sprache zur Beschreibung von Konsultationsphasen in Expertensystemen
- 1990-20 Y. Ortega Mallen, D. de Frutos Escrig: A Complete Proof System for Timed Observations
- 1990-21 * Manfred Nagl: Modelling of Software Architectures: Importance, Notions, Experiences
- 1990-22 H. Fassbender, H. Vogler: A Call-by-need Implementation of Syntax Directed Functional Programming

- 1991-01 Guenther Geiler (ed.), Fachgruppe Informatik: Jahresbericht 1990
- 1991-03 B. Steffen, A. Ingolfsdottir: Characteristic Formulae for Processes with Divergence
- 1991-04 M. Portz: A new class of cryptosystems based on interconnection networks
- 1991-05 H. Kuchen, G. Geiler: Distributed Applicative Arrays
- 1991-06 * Ludwig Staiger: Kolmogorov Complexity and Hausdorff Dimension
- 1991-07 * Ludwig Staiger: Syntactic Congruences for w-languages
- 1991-09 * Eila Kuikka: A Proposal for a Syntax-Directed Text Processing System
- 1991-10 K. Gladitz, H. Fassbender, H. Vogler: Compiler-based Implementation of Syntax-Directed Functional Programming
- 1991-11 R. Loogen, St. Winkler: Dynamic Detection of Determinism in Functional Logic Languages
- 1991-12 * K. Indermark, M. Rodriguez Artalejo (Eds.): Granada Workshop on the Integration of Functional and Logic Programming
- 1991-13 * Rolf Hager, Wolfgang Kremer: The Adaptive Priority Scheduler: A More Fair Priority Service Discipline
- 1991-14 * Andreas Fasbender, Wolfgang Kremer: A New Approximation Algorithm for Tandem Networks with Priority Nodes
- 1991-15 J. Börstler, A. Zündorf: Revisiting extensions to Modula-2 to support reusability
- 1991-16 J. Börstler, Th. Janning: Bridging the gap between Requirements Analysis and Design
- 1991-17 A. Zündorf, A. Schürr: Nondeterministic Control Structures for Graph Rewriting Systems
- 1991-18 * Matthias Jarke, John Mylopoulos, Joachim W. Schmidt, Yannis Vassiliou: DAIDA: An Environment for Evolving Information Systems
- 1991-19 M. Jeusfeld, M. Jarke: From Relational to Object-Oriented Integrity Simplification
- 1991-20 G. Hogen, A. Kindler, R. Loogen: Automatic Parallelization of Lazy Functional Programs
- 1991-21 * Prof. Dr. rer. nat. Otto Spaniol: ODP (Open Distributed Processing): Yet another Viewpoint
- 1991-22 H. Kuchen, F. Lücking, H. Stoltze: The Topology Description Language TDL
- 1991-23 S. Graf, B. Steffen: Compositional Minimization of Finite State Systems
- 1991-24 R. Cleaveland, J. Parrow, B. Steffen: The Concurrency Workbench: A Semantics Based Tool for the Verification of Concurrent Systems
- 1991-25 * Rudolf Mathar, Jürgen Mattfeldt: Optimal Transmission Ranges for Mobile Communication in Linear Multihop Packet Radio Networks
- 1991-26 M. Jeusfeld, M. Staudt: Query Optimization in Deductive Object Bases
- 1991-27 J. Knoop, B. Steffen: The Interprocedural Coincidence Theorem
- 1991-28 J. Knoop, B. Steffen: Unifying Strength Reduction and Semantic Code Motion
- 1991-30 T. Margaria: First-Order theories for the verification of complex FSMs
- 1991-31 B. Steffen: Generating Data Flow Analysis Algorithms from Modal Specifications
- 1992-01 Stefan Eherer (ed.), Fachgruppe Informatik: Jahresbericht 1991

- 1992-02 * Bernhard Westfechtel: Basismechanismen zur Datenverwaltung in strukturbezogenen Hypertextsystemen
- 1992-04 S. A. Smolka, B. Steffen: Priority as Extremal Probability
- 1992-05 * Matthias Jarke, Carlos Maltzahn, Thomas Rose: Sharing Processes: Team Coordination in Design Repositories
- 1992-06 O. Burkart, B. Steffen: Model Checking for Context-Free Processes
- 1992-07 * Matthias Jarke, Klaus Pohl: Information Systems Quality and Quality Information Systems
- 1992-08 * Rudolf Mathar, Jürgen Mattfeldt: Analyzing Routing Strategy NFP in Multihop Packet Radio Networks on a Line
- 1992-09 * Alfons Kemper, Guido Moerkotte: Grundlagen objektorientierter Datenbanksysteme
- 1992-10 Matthias Jarke, Manfred Jeusfeld, Andreas Miethsam, Michael Gocek: Towards a logic-based reconstruction of software configuration management
- 1992-11 Werner Hans: A Complete Indexing Scheme for WAM-based Abstract Machines
- 1992-12 W. Hans, R. Loogen, St. Winkler: On the Interaction of Lazy Evaluation and Backtracking
- 1992-13 * Matthias Jarke, Thomas Rose: Specification Management with CAD
- 1992-14 Th. Noll, H. Vogler: Top-down Parsing with Simultaneous Evaluation on Noncircular Attribute Grammars
- 1992-15 A. Schuerr, B. Westfechtel: Graphgrammatiken und Graphersetzungssysteme(written in german)
- 1992-16 * Graduiertenkolleg Informatik und Technik (Hrsg.): Forschungsprojekte des Graduiertenkollegs Informatik und Technik
- 1992-17 M. Jarke (ed.): ConceptBase V3.1 User Manual
- 1992-18 * Clarence A. Ellis, Matthias Jarke (Eds.): Distributed Cooperation in Integrated Information Systems - Proceedings of the Third International Workshop on Intelligent and Cooperative Information Systems
- 1992-19-00 H. Kuchen, R. Loogen (eds.): Proceedings of the 4th Int. Workshop on the Parallel Implementation of Functional Languages
- 1992-19-01 G. Hogen, R. Loogen: PASTEL - A Parallel Stack-Based Implementation of Eager Functional Programs with Lazy Data Structures (Extended Abstract)
- 1992-19-02 H. Kuchen, K. Gladitz: Implementing Bags on a Shared Memory MIMD-Machine
- 1992-19-03 C. Rathsack, S.B. Scholz: LISA - A Lazy Interpreter for a Full-Fledged Lambda-Calculus
- 1992-19-04 T.A. Bratvold: Determining Useful Parallelism in Higher Order Functions
- 1992-19-05 S. Kahrs: Polymorphic Type Checking by Interpretation of Code
- 1992-19-06 M. Chakravarty, M. Köhler: Equational Constraints, Residuation, and the Parallel JUMP-Machine
- 1992-19-07 J. Seward: Polymorphic Strictness Analysis using Frontiers (Draft Version)
- 1992-19-08 D. Gärtner, A. Kimms, W. Kluge: pi-Red⁺ - A Compiling Graph-Reduction System for a Full Fledged Lambda-Calculus

- 1992-19-09 D. Howe, G. Burn: Experiments with strict STG code
- 1992-19-10 J. Glauert: Parallel Implementation of Functional Languages Using Small Processes
- 1992-19-11 M. Joy, T. Axford: A Parallel Graph Reduction Machine
- 1992-19-12 A. Bennett, P. Kelly: Simulation of Multicache Parallel Reduction
- 1992-19-13 K. Langendoen, D.J. Agterkamp: Cache Behaviour of Lazy Functional Programs (Working Paper)
- 1992-19-14 K. Hammond, S. Peyton Jones: Profiling scheduling strategies on the GRIP parallel reducer
- 1992-19-15 S. Mintchev: Using Strictness Information in the STG-machine
- 1992-19-16 D. Rushall: An Attribute Grammar Evaluator in Haskell
- 1992-19-17 J. Wild, H. Glaser, P. Hartel: Statistics on storage management in a lazy functional language implementation
- 1992-19-18 W.S. Martins: Parallel Implementations of Functional Languages
- 1992-19-19 D. Lester: Distributed Garbage Collection of Cyclic Structures (Draft version)
- 1992-19-20 J.C. Glas, R.F.H. Hofman, W.G. Vree: Parallelization of Branch-and-Bound Algorithms in a Functional Programming Environment
- 1992-19-21 S. Hwang, D. Rushall: The nu-STG machine: a parallelized Spineless Tagless Graph Reduction Machine in a distributed memory architecture (Draft version)
- 1992-19-22 G. Burn, D. Le Metayer: Cps-Translation and the Correctness of Optimising Compilers
- 1992-19-23 S.L. Peyton Jones, P. Wadler: Imperative functional programming (Brief summary)
- 1992-19-24 W. Damm, F. Liu, Th. Peikenkamp: Evaluation and Parallelization of Functions in Functional + Logic Languages (abstract)
- 1992-19-25 M. Kessler: Communication Issues Regarding Parallel Functional Graph Rewriting
- 1992-19-26 Th. Peikenkamp: Charakterizing and representing neededness in functional logic languages (abstract)
- 1992-19-27 H. Doerr: Monitoring with Graph-Grammars as formal operational Models
- 1992-19-28 J. van Groningen: Some implementation aspects of Concurrent Clean on distributed memory architectures
- 1992-19-29 G. Ostheimer: Load Bounding for Implicit Parallelism (abstract)
- 1992-20 H. Kuchen, F.J. Lopez Fraguas, J.J. Moreno Navarro, M. Rodriguez Artalejo: Implementing Disequality in a Lazy Functional Logic Language
- 1992-21 H. Kuchen, F.J. Lopez Fraguas: Result Directed Computing in a Functional Logic Language
- 1992-22 H. Kuchen, J.J. Moreno Navarro, M.V. Hermenegildo: Independent AND-Parallel Narrowing
- 1992-23 T. Margaria, B. Steffen: Distinguishing Formulas for Free
- 1992-24 K. Pohl: The Three Dimensions of Requirements Engineering
- 1992-25 * R. Stainov: A Dynamic Configuration Facility for Multimedia Communications
- 1992-26 * Michael von der Beeck: Integration of Structured Analysis and Timed Statecharts for Real-Time and Concurrency Specification

- 1992-27 W. Hans, St. Winkler: Aliasing and Groundness Analysis of Logic Programs through Abstract Interpretation and its Safety
- 1992-28 * Gerhard Steinke, Matthias Jarke: Support for Security Modeling in Information Systems Design
- 1992-29 B. Schinzel: Warum Frauenforschung in Naturwissenschaft und Technik
- 1992-30 A. Kemper, G. Moerkotte, K. Peithner: Object-Oriented Axiomatized by Dynamic Logic
- 1992-32 * Bernd Heinrichs, Kai Jakobs: Timer Handling in High-Performance Transport Systems
- 1992-33 * B. Heinrichs, K. Jakobs, K. Lenßen, W. Reinhardt, A. Spinner: Euro-Bridge: Communication Services for Multimedia Applications
- 1992-34 C. Gerlhof, A. Kemper, Ch. Kilger, G. Moerkotte: Partition-Based Clustering in Object Bases: From Theory to Practice
- 1992-35 J. Börstler: Feature-Oriented Classification and Reuse in IPSEN
- 1992-36 M. Jarke, J. Bubenko, C. Rolland, A. Sutcliffe, Y. Vassiliou: Theories Underlying Requirements Engineering: An Overview of NATURE at Genesis
- 1992-37 * K. Pohl, M. Jarke: Quality Information Systems: Repository Support for Evolving Process Models
- 1992-38 A. Zuendorf: Implementation of the imperative / rule based language PROGRES
- 1992-39 P. Koch: Intelligentes Backtracking bei der Auswertung funktional-logischer Programme
- 1992-40 * Rudolf Mathar, Jürgen Mattfeldt: Channel Assignment in Cellular Radio Networks
- 1992-41 * Gerhard Friedrich, Wolfgang Neidl: Constructive Utility in Model-Based Diagnosis Repair Systems
- 1992-42 * P. S. Chen, R. Hennicker, M. Jarke: On the Retrieval of Reusable Software Components
- 1992-43 W. Hans, St. Winkler: Abstract Interpretation of Functional Logic Languages
- 1992-44 N. Kiesel, A. Schuerr, B. Westfechtel: Design and Evaluation of GRAS, a Graph-Oriented Database System for Engineering Applications
- 1993-01 * Fachgruppe Informatik: Jahresbericht 1992
- 1993-02 * Patrick Shicheng Chen: On Inference Rules of Logic-Based Information Retrieval Systems
- 1993-03 G. Hogen, R. Loogen: A New Stack Technique for the Management of Runtime Structures in Distributed Environments
- 1993-05 A. Zündorf: A Heuristic for the Subgraph Isomorphism Problem in Executing PROGRES
- 1993-06 A. Kemper, D. Kossmann: Adaptable Pointer Swizzling Strategies in Object Bases: Design, Realization, and Quantitative Analysis
- 1993-07 * Graduiertenkolleg Informatik und Technik (Hrsg.): Graduiertenkolleg Informatik und Technik
- 1993-08 * Matthias Berger: k-Coloring Vertices using a Neural Network with Convergence to Valid Solutions
- 1993-09 M. Buchheit, M. Jeusfeld, W. Nutt, M. Staudt: Subsumption between Queries to Object-Oriented Databases

- 1993-10 O. Burkart, B. Steffen: Pushdown Processes: Parallel Composition and Model Checking
- 1993-11 * R. Große-Wienker, O. Hermanns, D. Menzenbach, A. Pollacks, S. Repetzki, J. Schwartz, K. Sonnenschein, B. Westfechtel: Das SUKITS-Projekt: A-posteriori-Integration heterogener CIM-Anwendungssysteme
- 1993-12 * Rudolf Mathar, Jürgen Mattfeldt: On the Distribution of Cumulated Interference Power in Rayleigh Fading Channels
- 1993-13 O. Maler, L. Staiger: On Syntactic Congruences for omega-languages
- 1993-14 M. Jarke, St. Eherer, R. Gellersdoerfer, M. Jeusfeld, M. Staudt: ConceptBase - A Deductive Object Base Manager
- 1993-15 M. Staudt, H.W. Nissen, M.A. Jeusfeld: Query by Class, Rule and Concept
- 1993-16 * M. Jarke, K. Pohl, St. Jacobs et al.: Requirements Engineering: An Integrated View of Representation Process and Domain
- 1993-17 * M. Jarke, K. Pohl: Establishing Vision in Context: Towards a Model of Requirements Processes
- 1993-18 W. Hans, H. Kuchen, St. Winkler: Full Indexing for Lazy Narrowing
- 1993-19 W. Hans, J.J. Ruz, F. Saenz, St. Winkler: A VHDL Specification of a Shared Memory Parallel Machine for Babel
- 1993-20 * K. Finke, M. Jarke, P. Szczerko, R. Soltysiak: Quality Management for Expert Systems in Process Control
- 1993-21 M. Jarke, M.A. Jeusfeld, P. Szczerko: Three Aspects of Intelligent Cooperation in the Quality Cycle
- 1994-01 Margit Generet, Sven Martin (eds.), Fachgruppe Informatik: Jahresbericht 1993
- 1994-02 M. Lefering: Development of Incremental Integration Tools Using Formal Specifications
- 1994-03 * P. Constantopoulos, M. Jarke, J. Mylopoulos, Y. Vassiliou: The Software Information Base: A Server for Reuse
- 1994-04 * Rolf Hager, Rudolf Mathar, Jürgen Mattfeldt: Intelligent Cruise Control and Reliable Communication of Mobile Stations
- 1994-05 * Rolf Hager, Peter Hermesmann, Michael Portz: Feasibility of Authentication Procedures within Advanced Transport Telematics
- 1994-06 * Claudia Popien, Bernd Meyer, Axel Kuepper: A Formal Approach to Service Import in ODP Trader Federations
- 1994-07 P. Peters, P. Szczerko: Integrating Models of Quality Management Methods by an Object-Oriented Repository
- 1994-08 * Manfred Nagl, Bernhard Westfechtel: A Universal Component for the Administration in Distributed and Integrated Development Environments
- 1994-09 * Patrick Horster, Holger Petersen: Signatur- und Authentifikationsverfahren auf der Basis des diskreten Logarithmusproblems
- 1994-11 A. Schürr: PROGRES, A Visual Language and Environment for Programming with Graph REwrite Systems
- 1994-12 A. Schürr: Specification of Graph Translators with Triple Graph Grammars
- 1994-13 A. Schürr: Logic Based Programmed Structure Rewriting Systems
- 1994-14 L. Staiger: Codes, Simplifying Words, and Open Set Condition

- 1994-15 * Bernhard Westfechtel: A Graph-Based System for Managing Configurations of Engineering Design Documents
- 1994-16 P. Klein: Designing Software with Modula-3
- 1994-17 I. Litovsky, L. Staiger: Finite acceptance of infinite words
- 1994-18 G. Hogen, R. Loogen: Parallel Functional Implementations: Graphbased vs. Stackbased Reduction
- 1994-19 M. Jeusfeld, U. Johnen: An Executable Meta Model for Re-Engineering of Database Schemas
- 1994-20 * R. Gallersdörfer, M. Jarke, K. Klabunde: Intelligent Networks as a Data Intensive Application (INDIA)
- 1994-21 M. Mohnen: Proving the Correctness of the Static Link Technique Using Evolving Algebras
- 1994-22 H. Fernau, L. Staiger: Valuations and Unambiguity of Languages, with Applications to Fractal Geometry
- 1994-24 * M. Jarke, K. Pohl, R. Dömges, St. Jacobs, H. W. Nissen: Requirements Information Management: The NATURE Approach
- 1994-25 * M. Jarke, K. Pohl, C. Rolland, J.-R. Schmitt: Experience-Based Method Evaluation and Improvement: A Process Modeling Approach
- 1994-26 * St. Jacobs, St. Kethers: Improving Communication and Decision Making within Quality Function Deployment
- 1994-27 * M. Jarke, H. W. Nissen, K. Pohl: Tool Integration in Evolving Information Systems Environments
- 1994-28 O. Burkart, D. Caucal, B. Steffen: An Elementary Bisimulation Decision Procedure for Arbitrary Context-Free Processes
- 1995-01 * Fachgruppe Informatik: Jahresbericht 1994
- 1995-02 Andy Schürr, Andreas J. Winter, Albert Zündorf: Graph Grammar Engineering with PROGRES
- 1995-03 Ludwig Staiger: A Tight Upper Bound on Kolmogorov Complexity by Hausdorff Dimension and Uniformly Optimal Prediction
- 1995-04 Birgitta König-Ries, Sven Helmer, Guido Moerkotte: An experimental study on the complexity of left-deep join ordering problems for cyclic queries
- 1995-05 Sophie Cluet, Guido Moerkotte: Efficient Evaluation of Aggregates on Bulk Types
- 1995-06 Sophie Cluet, Guido Moerkotte: Nested Queries in Object Bases
- 1995-07 Sophie Cluet, Guido Moerkotte: Query Optimization Techniques Exploiting Class Hierarchies
- 1995-08 Markus Mohnen: Efficient Compile-Time Garbage Collection for Arbitrary Data Structures
- 1995-09 Markus Mohnen: Functional Specification of Imperative Programs: An Alternative Point of View of Functional Languages
- 1995-10 Rainer Gallersdörfer, Matthias Nicola: Improving Performance in Replicated Databases through Relaxed Coherency
- 1995-11 * M.Staudt, K.von Thadden: Subsumption Checking in Knowledge Bases
- 1995-12 * G.V.Zemanek, H.W.Nissen, H.Hubert, M.Jarke: Requirements Analysis from Multiple Perspectives: Experiences with Conceptual Modeling Technology

- 1995-13 * M.Staudt, M.Jarke: Incremental Maintenance of Externally Materialized Views
- 1995-14 * P.Peters, P.Szczurko, M.Jeusfeld: Oriented Information Management: Conceptual Models at Work
- 1995-15 * Matthias Jarke, Sudha Ram (Hrsg.): WITS 95 Proceedings of the 5th Annual Workshop on Information Technologies and Systems
- 1995-16 * W.Hans, St.Winkler, F.Saenz: Distributed Execution in Functional Logic Programming
- 1996-01 * Jahresbericht 1995
- 1996-02 Michael Hanus, Christian Prehofer: Higher-Order Narrowing with Definitional Trees
- 1996-03 * W.Scheufele, G.Moerkotte: Optimal Ordering of Selections and Joins in Acyclic Queries with Expensive Predicates
- 1996-04 Klaus Pohl: PRO-ART: Enabling Requirements Pre-Traceability
- 1996-05 Klaus Pohl: Requirements Engineering: An Overview
- 1996-06 * M.Jarke, W.Marquardt: Design and Evaluation of Computer-Aided Process Modelling Tools
- 1996-07 Olaf Chitil: The Sigma-Semantics: A Comprehensive Semantics for Functional Programs
- 1996-08 * S.Sripada: On Entropy and the Limitations of the Second Law of Thermodynamics
- 1996-09 Michael Hanus (Ed.): Proceedings of the Poster Session of ALP96 - Fifth International Conference on Algebraic and Logic Programming
- 1996-09-0 Michael Hanus (Ed.): Proceedings of the Poster Session of ALP 96 - Fifth International Conference on Algebraic and Logic Programming: Introduction and table of contents
- 1996-09-1 Ilies Alouini: An Implementation of Conditional Concurrent Rewriting on Distributed Memory Machines
- 1996-09-2 Olivier Danvy, Karoline Malmkjær: On the Idempotence of the CPS Transformation
- 1996-09-3 Víctor M. Gulías, José L. Freire: Concurrent Programming in Haskell
- 1996-09-4 Sébastien Limet, Pierre Réty: On Decidability of Unifiability Modulo Rewrite Systems
- 1996-09-5 Alexandre Tessier: Declarative Debugging in Constraint Logic Programming
- 1996-10 Reidar Conradi, Bernhard Westfechtel: Version Models for Software Configuration Management
- 1996-11 * C.Weise, D.Lenzkes: A Fast Decision Algorithm for Timed Refinement
- 1996-12 * R.Dömges, K.Pohl, M.Jarke, B.Lohmann, W.Marquardt: PRO-ART/CE* — An Environment for Managing the Evolution of Chemical Process Simulation Models
- 1996-13 * K.Pohl, R.Klamma, K.Weidenhaupt, R.Dömges, P.Haumer, M.Jarke: A Framework for Process-Integrated Tools
- 1996-14 * R.Gallersdörfer, K.Klabunde, A.Stolz, M.Eßmajor: INDIA — Intelligent Networks as a Data Intensive Application, Final Project Report, June 1996
- 1996-15 * H.Schimpe, M.Staudt: VAREX: An Environment for Validating and Refining Rule Bases

- 1996-16 * M.Jarke, M.Gebhardt, S.Jacobs, H.Nissen: Conflict Analysis Across Heterogeneous Viewpoints: Formalization and Visualization
- 1996-17 Manfred A. Jeusfeld, Tung X. Bui: Decision Support Components on the Internet
- 1996-18 Manfred A. Jeusfeld, Mike Papazoglou: Information Brokering: Design, Search and Transformation
- 1996-19 * P.Peters, M.Jarke: Simulating the impact of information flows in networked organizations
- 1996-20 Matthias Jarke, Peter Peters, Manfred A. Jeusfeld: Model-driven planning and design of cooperative information systems
- 1996-21 * G.de Michelis, E.Dubois, M.Jarke, F.Matthes, J.Mylopoulos, K.Pohl, J.Schmidt, C.Woo, E.Yu: Cooperative information systems: a manifesto
- 1996-22 * S.Jacobs, M.Gebhardt, S.Kethers, W.Rzasa: Filling HTML forms simultaneously: CoWeb architecture and functionality
- 1996-23 * M.Gebhardt, S.Jacobs: Conflict Management in Design
- 1997-01 Michael Hanus, Frank Zartmann (eds.): Jahresbericht 1996
- 1997-02 Johannes Faassen: Using full parallel Boltzmann Machines for Optimization
- 1997-03 Andreas Winter, Andy Schürr: Modules and Updatable Graph Views for PROGRAMMED Graph REwriting Systems
- 1997-04 Markus Mohnen, Stefan Tobies: Implementing Context Patterns in the Glasgow Haskell Compiler
- 1997-05 * S.Gruner: Schemakorrespondenzaxiome unterstützen die paargrammatische Spezifikation inkrementeller Integrationswerkzeuge
- 1997-06 Matthias Nicola, Matthias Jarke: Design and Evaluation of Wireless Health Care Information Systems in Developing Countries
- 1997-07 Petra Hofstedt: Taskparallele Skelette für irregulär strukturierte Probleme in deklarativen Sprachen
- 1997-08 Dorothea Blostein, Andy Schürr: Computing with Graphs and Graph Rewriting
- 1997-09 Carl-Arndt Krapp, Bernhard Westfechtel: Feedback Handling in Dynamic Task Nets
- 1997-10 Matthias Nicola, Matthias Jarke: Integrating Replication and Communication in Performance Models of Distributed Databases
- 1997-11 * R. Klamma, P. Peters, M. Jarke: Workflow Support for Failure Management in Federated Organizations
- 1997-13 Markus Mohnen: Optimising the Memory Management of Higher-Order Functional Programs
- 1997-14 Roland Baumann: Client/Server Distribution in a Structure-Oriented Database Management System
- 1997-15 George Botorog: High-Level Parallel Programming and the Efficient Implementation of Numerical Algorithms
- 1998-01 * Fachgruppe Informatik: Jahresbericht 1997
- 1998-02 Stefan Gruner, Manfred Nagel, Andy Schürr: Fine-grained and Structure-Oriented Document Integration Tools are Needed for Development Processes

- 1998-03 Stefan Gruner: Einige Anmerkungen zur graphgrammatischen Spezifikation von Integrationswerkzeugen nach Westfechtel, Janning, Lefering und Schürr
- 1998-04 * O. Kubitz: Mobile Robots in Dynamic Environments
- 1998-05 Martin Leucker, Stephan Tobies: Truth - A Verification Platform for Distributed Systems
- 1998-06 * Matthias Oliver Berger: DECT in the Factory of the Future
- 1998-07 M. Arnold, M. Erdmann, M. Glinz, P. Haumer, R. Knoll, B. Paech, K. Pohl, J. Ryser, R. Studer, K. Weidenhaupt: Survey on the Scenario Use in Twelve Selected Industrial Projects
- 1998-09 * Th. Lehmann: Geometrische Ausrichtung medizinischer Bilder am Beispiel intraoraler Radiographien
- 1998-10 * M. Nicola, M. Jarke: Performance Modeling of Distributed and Replicated Databases
- 1998-11 * Ansgar Schleicher, Bernhard Westfechtel, Dirk Jäger: Modeling Dynamic Software Processes in UML
- 1998-12 * W. Appelt, M. Jarke: Interoperable Tools for Cooperation Support using the World Wide Web
- 1998-13 Klaus Indermark: Semantik rekursiver Funktionsdefinitionen mit Striktheitsinformation
- 1999-01 * Jahresbericht 1998
- 1999-02 * F. Huch: Verification of Erlang Programs using Abstract Interpretation and Model Checking — Extended Version
- 1999-03 * R. Gallersdörfer, M. Jarke, M. Nicola: The ADR Replication Manager
- 1999-04 María Alpuente, Michael Hanus, Salvador Lucas, Germán Vidal: Specialization of Functional Logic Programs Based on Needed Narrowing
- 1999-05 * W. Thomas (Ed.): DLT 99 - Developments in Language Theory Fourth International Conference
- 1999-06 * Kai Jakobs, Klaus-Dieter Kleefeld: Informationssysteme für die angewandte historische Geographie
- 1999-07 Thomas Wilke: CTL+ is exponentially more succinct than CTL
- 1999-08 Oliver Matz: Dot-Depth and Monadic Quantifier Alternation over Pictures
- 2000-01 * Jahresbericht 1999
- 2000-02 Jens Vöge, Marcin Jurdzinski A Discrete Strategy Improvement Algorithm for Solving Parity Games
- 2000-03 D. Jäger, A. Schleicher, B. Westfechtel: UPGRADE: A Framework for Building Graph-Based Software Engineering Tools
- 2000-04 Andreas Becks, Stefan Sklorz, Matthias Jarke: Exploring the Semantic Structure of Technical Document Collections: A Cooperative Systems Approach
- 2000-05 Mareike Schoop: Cooperative Document Management
- 2000-06 Mareike Schoop, Christoph Quix (eds.): Proceedings of the Fifth International Workshop on the Language-Action Perspective on Communication Modelling
- 2000-07 * Markus Mohnen, Pieter Koopman (Eds.): Proceedings of the 12th International Workshop of Functional Languages

- 2000-08 Thomas Arts, Thomas Noll: Verifying Generic Erlang Client-Server Implementations
- 2001-01 * Jahresbericht 2000
- 2001-02 Benedikt Bollig, Martin Leucker: Deciding LTL over Mazurkiewicz Traces
- 2001-03 Thierry Cachat: The power of one-letter rational languages
- 2001-04 Benedikt Bollig, Martin Leucker, Michael Weber: Local Parallel Model Checking for the Alternation Free μ -Calculus
- 2001-05 Benedikt Bollig, Martin Leucker, Thomas Noll: Regular MSC Languages
- 2001-06 Achim Blumensath: Prefix-Recognisable Graphs and Monadic Second-Order Logic
- 2001-07 Martin Grohe, Stefan Wöhrle: An Existential Locality Theorem
- 2001-08 Mareike Schoop, James Taylor (eds.): Proceedings of the Sixth International Workshop on the Language-Action Perspective on Communication Modelling
- 2001-09 Thomas Arts, Jürgen Giesl: A collection of examples for termination of term rewriting using dependency pairs
- 2001-10 Achim Blumensath: Axiomatising Tree-interpretable Structures
- 2001-11 Klaus Indermark, Thomas Noll (eds.): Kolloquium Programmiersprachen und Grundlagen der Programmierung
- 2002-01 * Jahresbericht 2001
- 2002-02 Jürgen Giesl, Aart Middeldorp: Transformation Techniques for Context-Sensitive Rewrite Systems
- 2002-03 Benedikt Bollig, Martin Leucker, Thomas Noll: Generalised Regular MSC Languages
- 2002-04 Jürgen Giesl, Aart Middeldorp: Innermost Termination of Context-Sensitive Rewriting
- 2002-05 Horst Lichter, Thomas von der Maßen, Thomas Weiler: Modelling Requirements and Architectures for Software Product Lines
- 2002-06 Henry N. Adorna: 3-Party Message Complexity is Better than 2-Party Ones for Proving Lower Bounds on the Size of Minimal Nondeterministic Finite Automata
- 2002-07 Jörg Dahmen: Invariant Image Object Recognition using Gaussian Mixture Densities
- 2002-08 Markus Mohnen: An Open Framework for Data-Flow Analysis in Java
- 2002-09 Markus Mohnen: Interfaces with Default Implementations in Java
- 2002-10 Martin Leucker: Logics for Mazurkiewicz traces
- 2002-11 Jürgen Giesl, Hans Zantema: Liveness in Rewriting
- 2003-01 * Jahresbericht 2002
- 2003-02 Jürgen Giesl, René Thiemann: Size-Change Termination for Term Rewriting
- 2003-03 Jürgen Giesl, Deepak Kapur: Deciding Inductive Validity of Equations
- 2003-04 Jürgen Giesl, René Thiemann, Peter Schneider-Kamp, Stephan Falke: Improving Dependency Pairs
- 2003-05 Christof Löding, Philipp Rohde: Solving the Sabotage Game is PSPACE-hard
- 2003-06 Franz Josef Och: Statistical Machine Translation: From Single-Word Models to Alignment Templates

- 2003-07 Horst Lichter, Thomas von der Maßen, Alexander Nyßen, Thomas Weiler: Vergleich von Ansätzen zur Feature Modellierung bei der Softwareproduktlinienentwicklung
- 2003-08 Jürgen Giesl, René Thiemann, Peter Schneider-Kamp, Stephan Falke: Mechanizing Dependency Pairs
- 2004-01 * Fachgruppe Informatik: Jahresbericht 2003
- 2004-02 Benedikt Bollig, Martin Leucker: Message-Passing Automata are expressively equivalent to EMSO logic
- 2004-03 Delia Kesner, Femke van Raamsdonk, Joe Wells (eds.): HOR 2004 – 2nd International Workshop on Higher-Order Rewriting
- 2004-04 Slim Abdennadher, Christophe Ringeissen (eds.): RULE 04 – Fifth International Workshop on Rule-Based Programming
- 2004-05 Herbert Kuchen (ed.): WFLP 04 – 13th International Workshop on Functional and (Constraint) Logic Programming
- 2004-06 Sergio Antoy, Yoshihito Toyama (eds.): WRS 04 – 4th International Workshop on Reduction Strategies in Rewriting and Programming
- 2004-07 Michael Codish, Aart Middeldorp (eds.): WST 04 – 7th International Workshop on Termination
- 2004-08 Klaus Indermark, Thomas Noll: Algebraic Correctness Proofs for Compiling Recursive Function Definitions with Strictness Information
- 2004-09 Joachim Kneis, Daniel Mölle, Stefan Richter, Peter Rossmanith: Parameterized Power Domination Complexity
- 2004-10 Zinaida Benenson, Felix C. Gärtner, Dogan Kesdogan: Secure Multi-Party Computation with Security Modules
- 2005-01 * Fachgruppe Informatik: Jahresbericht 2004
- 2005-02 Maximillian Dornseif, Felix C. Gärtner, Thorsten Holz, Martin Mink: An Offensive Approach to Teaching Information Security: “Aachen Summer School Applied IT Security”
- 2005-03 Jürgen Giesl, René Thiemann, Peter Schneider-Kamp: Proving and Disproving Termination of Higher-Order Functions
- 2005-04 Daniel Mölle, Stefan Richter, Peter Rossmanith: A Faster Algorithm for the Steiner Tree Problem
- 2005-05 Fabien Pouget, Thorsten Holz: A Pointillist Approach for Comparing Honey pots
- 2005-06 Simon Fischer, Berthold Vöcking: Adaptive Routing with Stale Information
- 2005-07 Felix C. Freiling, Thorsten Holz, Georg Wicherski: Botnet Tracking: Exploring a Root-Cause Methodology to Prevent Distributed Denial-of-Service Attacks
- 2005-08 Joachim Kneis, Peter Rossmanith: A New Satisfiability Algorithm With Applications To Max-Cut
- 2005-09 Klaus Kursawe, Felix C. Freiling: Byzantine Fault Tolerance on General Hybrid Adversary Structures
- 2005-10 Benedikt Bollig: Automata and Logics for Message Sequence Charts
- 2005-11 Simon Fischer, Berthold Vöcking: A Counterexample to the Fully Mixed Nash Equilibrium Conjecture

- 2005-12 Neeraj Mittal, Felix Freiling, S. Venkatesan, Lucia Draque Penso: Efficient Reductions for Wait-Free Termination Detection in Faulty Distributed Systems
- 2005-13 Carole Delporte-Gallet, Hugues Fauconnier, Felix C. Freiling: Revisiting Failure Detection and Consensus in Omission Failure Environments
- 2005-14 Felix C. Freiling, Sukumar Ghosh: Code Stabilization
- 2005-15 Uwe Naumann: The Complexity of Derivative Computation
- 2005-16 Uwe Naumann: Syntax-Directed Derivative Code (Part I: Tangent-Linear Code)
- 2005-17 Uwe Naumann: Syntax-directed Derivative Code (Part II: Intraprocedural Adjoint Code)
- 2005-18 Thomas von der Maßen, Klaus Müller, John MacGregor, Eva Geisberger, Jörg Dörr, Frank Houdek, Harbhajan Singh, Holger Wußmann, Hans-Veit Bacher, Barbara Paech: Einsatz von Features im Software-Entwicklungsprozess - Abschlußbericht des GI-Arbeitskreises "Features"
- 2005-19 Uwe Naumann, Andre Vehreschild: Tangent-Linear Code by Augmented LL-Parsers
- 2005-20 Felix C. Freiling, Martin Mink: Bericht über den Workshop zur Ausbildung im Bereich IT-Sicherheit Hochschulausbildung, berufliche Weiterbildung, Zertifizierung von Ausbildungsangeboten am 11. und 12. August 2005 in Köln organisiert von RWTH Aachen in Kooperation mit BITKOM, BSI, DLR und Gesellschaft fuer Informatik (GI) e.V.
- 2005-21 Thomas Noll, Stefan Rieger: Optimization of Straight-Line Code Revisited
- 2005-22 Felix Freiling, Maurice Herlihy, Lucia Draque Penso: Optimal Randomized Fair Exchange with Secret Shared Coins
- 2005-23 Heiner Ackermann, Alantha Newman, Heiko Röglin, Berthold Vöcking: Decision Making Based on Approximate and Smoothed Pareto Curves
- 2005-24 Alexander Becher, Zinaida Benenson, Maximillian Dornseif: Tampering with Motes: Real-World Physical Attacks on Wireless Sensor Networks
- 2006-01 * Fachgruppe Informatik: Jahresbericht 2005
- 2006-02 Michael Weber: Parallel Algorithms for Verification of Large Systems
- 2006-03 Michael Maier, Uwe Naumann: Intraprocedural Adjoint Code Generated by the Differentiation-Enabled NAGWare Fortran Compiler
- 2006-04 Ebadollah Varnik, Uwe Naumann, Andrew Lyons: Toward Low Static Memory Jacobian Accumulation
- 2006-05 Uwe Naumann, Jean Utke, Patrick Heimbach, Chris Hill, Derya Ozyurt, Carl Wunsch, Mike Fagan, Nathan Tallent, Michelle Strout: Adjoint Code by Source Transformation with OpenAD/F
- 2006-06 Joachim Kneis, Daniel Mölle, Stefan Richter, Peter Rossmanith: Divide-and-Color
- 2006-07 Thomas Colcombet, Christof Löding: Transforming structures by set interpretations
- 2006-08 Uwe Naumann, Yuxiao Hu: Optimal Vertex Elimination in Single-Expression-Use Graphs
- 2006-09 Tingting Han, Joost-Pieter Katoen: Counterexamples in Probabilistic Model Checking

- 2006-10 Mesut Günes, Alexander Zimmermann, Martin Wenig, Jan Ritterfeld, Ulrich Meis: From Simulations to Testbeds - Architecture of the Hybrid MCG-Mesh Testbed
- 2006-11 Bastian Schlich, Michael Rohrbach, Michael Weber, Stefan Kowalewski: Model Checking Software for Microcontrollers
- 2006-12 Benedikt Bollig, Joost-Pieter Katoen, Carsten Kern, Martin Leucker: Replaying Play in and Play out: Synthesis of Design Models from Scenarios by Learning
- 2006-13 Wong Karianto, Christof Löding: Unranked Tree Automata with Sibling Equalities and Disequalities
- 2006-14 Danilo Beuche, Andreas Birk, Heinrich Dreier, Andreas Fleischmann, Heidi Galle, Gerald Heller, Dirk Janzen, Isabel John, Ramin Tavakoli Kolagari, Thomas von der Maßen, Andreas Wolfram: Report of the GI Work Group “Requirements Management Tools for Product Line Engineering”
- 2006-15 Sebastian Ullrich, Jakob T. Valvoda, Torsten Kuhlen: Utilizing optical sensors from mice for new input devices
- 2006-16 Rafael Ballagas, Jan Borchers: Selexels: a Conceptual Framework for Pointing Devices with Low Expressiveness
- 2006-17 Eric Lee, Henning Kiel, Jan Borchers: Scrolling Through Time: Improving Interfaces for Searching and Navigating Continuous Audio Timelines
- 2007-01 * Fachgruppe Informatik: Jahresbericht 2006
- 2007-02 Carsten Fuhs, Jürgen Giesl, Aart Middeldorp, Peter Schneider-Kamp, René Thiemann, and Harald Zankl: SAT Solving for Termination Analysis with Polynomial Interpretations
- 2007-03 Jürgen Giesl, René Thiemann, Stephan Swiderski, and Peter Schneider-Kamp: Proving Termination by Bounded Increase
- 2007-04 Jan Buchholz, Eric Lee, Jonathan Klein, and Jan Borchers: coJIVE: A System to Support Collaborative Jazz Improvisation
- 2007-05 Uwe Naumann: On Optimal DAG Reversal
- 2007-06 Joost-Pieter Katoen, Thomas Noll, and Stefan Rieger: Verifying Concurrent List-Manipulating Programs by LTL Model Checking
- 2007-07 Alexander Nyßen, Horst Lichter: MeDUSA - Method for UML2-based Design of Embedded Software Applications
- 2007-08 Falk Salewski and Stefan Kowalewski: Achieving Highly Reliable Embedded Software: An empirical evaluation of different approaches
- 2007-09 Tina Krauß, Heiko Mantel, and Henning Sudbrock: A Probabilistic Justification of the Combining Calculus under the Uniform Scheduler Assumption
- 2007-10 Martin Neuhäüßer, Joost-Pieter Katoen: Bisimulation and Logical Preservation for Continuous-Time Markov Decision Processes
- 2007-11 Klaus Wehrle (editor): 6. Fachgespräch Sensornetzwerke
- 2007-12 Uwe Naumann: An L-Attributed Grammar for Adjoint Code
- 2007-13 Uwe Naumann, Michael Maier, Jan Riehme, and Bruce Christianson: Second-Order Adjoints by Source Code Manipulation of Numerical Programs

- 2007-14 Jean Utke, Uwe Naumann, Mike Fagan, Nathan Tallent, Michelle Strout, Patrick Heimbach, Chris Hill, and Carl Wunsch: OpenAD/F: A Modular, Open-Source Tool for Automatic Differentiation of Fortran Codes
- 2007-15 Volker Stolz: Temporal assertions for sequential and concurrent programs
- 2007-16 Sadeq Ali Makram, Mesut Güneç, Martin Wenig, Alexander Zimmermann: Adaptive Channel Assignment to Support QoS and Load Balancing for Wireless Mesh Networks
- 2007-17 René Thiemann: The DP Framework for Proving Termination of Term Rewriting
- 2007-18 Uwe Naumann: Call Tree Reversal is NP-Complete
- 2007-19 Jan Riehme, Andrea Walther, Jörg Stiller, Uwe Naumann: Adjoints for Time-Dependent Optimal Control
- 2007-20 Joost-Pieter Katoen, Daniel Klink, Martin Leucker, and Verena Wolf: Three-Valued Abstraction for Probabilistic Systems
- 2007-21 Tingting Han, Joost-Pieter Katoen, and Alexandru Mereacre: Compositional Modeling and Minimization of Time-Inhomogeneous Markov Chains
- 2007-22 Heiner Ackermann, Paul W. Goldberg, Vahab S. Mirrokni, Heiko Röglin, and Berthold Vöcking: Uncoordinated Two-Sided Markets
- 2008-01 * Fachgruppe Informatik: Jahresbericht 2007
- 2008-02 Henrik Bohnenkamp, Marielle Stoelinga: Quantitative Testing
- 2008-03 Carsten Fuhs, Jürgen Giesl, Aart Middeldorp, Peter Schneider-Kamp, René Thiemann, Harald Zankl: Maximal Termination
- 2008-04 Uwe Naumann, Jan Riehme: Sensitivity Analysis in Sisyphus with the AD-Enabled NAGWare Fortran Compiler
- 2008-05 Frank G. Radmacher: An Automata Theoretic Approach to the Theory of Rational Tree Relations
- 2008-06 Uwe Naumann, Laurent Hascoet, Chris Hill, Paul Hovland, Jan Riehme, Jean Utke: A Framework for Proving Correctness of Adjoint Message Passing Programs
- 2008-07 Alexander Nyßen, Horst Lichter: The MeDUSA Reference Manual, Second Edition
- 2008-08 George B. Mertzios, Stavros D. Nikolopoulos: The λ -cluster Problem on Parameterized Interval Graphs
- 2008-09 George B. Mertzios, Walter Unger: An optimal algorithm for the k-fixed-endpoint path cover on proper interval graphs
- 2008-10 George B. Mertzios, Walter Unger: Preemptive Scheduling of Equal-Length Jobs in Polynomial Time
- 2008-11 George B. Mertzios: Fast Convergence of Routing Games with Splittable Flows
- 2008-12 Joost-Pieter Katoen, Daniel Klink, Martin Leucker, Verena Wolf: Abstraction for stochastic systems by Erlang's method of stages
- 2008-13 Beatriz Alarcón, Fabian Emmes, Carsten Fuhs, Jürgen Giesl, Raúl Gutiérrez, Salvador Lucas, Peter Schneider-Kamp, René Thiemann: Improving Context-Sensitive Dependency Pairs
- 2008-14 Bastian Schlich: Model Checking of Software for Microcontrollers
- 2008-15 Joachim Kneis, Alexander Langer, Peter Rossmanith: A New Algorithm for Finding Trees with Many Leaves

- 2008-16 Hendrik vom Lehn, Elias Weingärtner and Klaus Wehrle: Comparing recent network simulators: A performance evaluation study
- 2008-17 Peter Schneider-Kamp: Static Termination Analysis for Prolog using Term Rewriting and SAT Solving
- 2008-18 Falk Salewski: Empirical Evaluations of Safety-Critical Embedded Systems
- 2008-19 Dirk Wilking: Empirical Studies for the Application of Agile Methods to Embedded Systems
- 2009-02 Taolue Chen, Tingting Han, Joost-Pieter Katoen, Alexandru Mereacre: Quantitative Model Checking of Continuous-Time Markov Chains Against Timed Automata Specifications
- 2009-03 Alexander Nyßen: Model-Based Construction of Embedded Real-Time Software - A Methodology for Small Devices
- 2009-04 Daniel Klünder: Entwurf eingebetteter Software mit abstrakten Zustandsmaschinen und Business Object Notation
- 2009-05 George B. Mertzios, Ignasi Sau, Shmuel Zaks: A New Intersection Model and Improved Algorithms for Tolerance Graphs
- 2009-06 George B. Mertzios, Ignasi Sau, Shmuel Zaks: The Recognition of Tolerance and Bounded Tolerance Graphs is NP-complete
- 2009-07 Joachim Kneis, Alexander Langer, Peter Rossmanith: Derandomizing Non-uniform Color-Coding I
- 2009-08 Joachim Kneis, Alexander Langer: Satellites and Mirrors for Solving Independent Set on Sparse Graphs
- 2009-09 Michael Nett: Implementation of an Automated Proof for an Algorithm Solving the Maximum Independent Set Problem
- 2009-10 Felix Reidl, Fernando Sánchez Villaamil: Automatic Verification of the Correctness of the Upper Bound of a Maximum Independent Set Algorithm
- 2009-11 Kyriaki Ioannidou, George B. Mertzios, Stavros D. Nikolopoulos: The Longest Path Problem is Polynomial on Interval Graphs
- 2009-12 Martin Neuhäüßer, Lijun Zhang: Time-Bounded Reachability in Continuous-Time Markov Decision Processes
- 2009-13 Martin Zimmermann: Time-optimal Winning Strategies for Poset Games
- 2009-14 Ralf Huuck, Gerwin Klein, Bastian Schlich (eds.): Doctoral Symposium on Systems Software Verification (DS SSV'09)
- 2009-15 Joost-Pieter Katoen, Daniel Klink, Martin Neuhäüßer: Compositional Abstraction for Stochastic Systems
- 2009-16 George B. Mertzios, Derek G. Corneil: Vertex Splitting and the Recognition of Trapezoid Graphs
- 2009-17 Carsten Kern: Learning Communicating and Nondeterministic Automata
- 2009-18 Paul Hänsch, Michaela Slaats, Wolfgang Thomas: Parametrized Regular Infinite Games and Higher-Order Pushdown Strategies
- 2010-02 Daniel Neider, Christof Löding: Learning Visibly One-Counter Automata in Polynomial Time
- 2010-03 Holger Krahn: MontiCore: Agile Entwicklung von domänenspezifischen Sprachen im Software-Engineering

- 2010-04 René Würzberger: Management dynamischer Geschäftsprozesse auf Basis statischer Prozessmanagementsysteme
- 2010-05 Daniel Retkowitz: Softwareunterstützung für adaptive eHome-Systeme
- 2010-06 Taolue Chen, Tingting Han, Joost-Pieter Katoen, Alexandru Mereacre: Computing maximum reachability probabilities in Markovian timed automata
- 2010-07 George B. Mertzios: A New Intersection Model for Multitolerance Graphs, Hierarchy, and Efficient Algorithms
- 2010-08 Carsten Otto, Marc Brockschmidt, Christian von Essen, Jürgen Giesl: Automated Termination Analysis of Java Bytecode by Term Rewriting
- 2010-09 George B. Mertzios, Shmuel Zaks: The Structure of the Intersection of Tolerance and Cocomparability Graphs
- 2010-10 Peter Schneider-Kamp, Jürgen Giesl, Thomas Ströder, Alexander Serebrenik, René Thiemann: Automated Termination Analysis for Logic Programs with Cut
- 2010-11 Martin Zimmermann: Parametric LTL Games
- 2010-12 Thomas Ströder, Peter Schneider-Kamp, Jürgen Giesl: Dependency Triples for Improving Termination Analysis of Logic Programs with Cut
- 2010-13 Ashraf Armoush: Design Patterns for Safety-Critical Embedded Systems
- 2010-14 Michael Codish, Carsten Fuhs, Jürgen Giesl, Peter Schneider-Kamp: Lazy Abstraction for Size-Change Termination
- 2010-15 Marc Brockschmidt, Carsten Otto, Christian von Essen, Jürgen Giesl: Termination Graphs for Java Bytecode
- 2010-16 Christian Berger: Automating Acceptance Tests for Sensor- and Actuator-based Systems on the Example of Autonomous Vehicles
- 2010-17 Hans Grönniger: Systemmodell-basierte Definition objektbasierter Modellierungssprachen mit semantischen Variationspunkten
- 2010-18 Ibrahim Armaç: Personalisierte eHomes: Mobilität, Privatsphäre und Sicherheit
- 2010-19 Felix Reidl: Experimental Evaluation of an Independent Set Algorithm
- 2010-20 Wladimir Fridman, Christof Löding, Martin Zimmermann: Degrees of Lookahead in Context-free Infinite Games
- 2011-02 Marc Brockschmidt, Carsten Otto, Jürgen Giesl: Modular Termination Proofs of Recursive Java Bytecode Programs by Term Rewriting
- 2011-03 Lars Noschinski, Fabian Emmes, Jürgen Giesl: A Dependency Pair Framework for Innermost Complexity Analysis of Term Rewrite Systems
- 2011-04 Christina Jansen, Jonathan Heinen, Joost-Pieter Katoen, Thomas Noll: A Local Greibach Normal Form for Hyperedge Replacement Grammars
- 2011-07 Shahar Maoz, Jan Oliver Ringert, Bernhard Rumpe: An Operational Semantics for Activity Diagrams using SMV
- 2011-08 Thomas Ströder, Fabian Emmes, Peter Schneider-Kamp, Jürgen Giesl, Carsten Fuhs: A Linear Operational Semantics for Termination and Complexity Analysis of ISO Prolog
- 2011-09 Markus Beckers, Johannes Lotz, Viktor Mosenkis, Uwe Naumann (Editors): Fifth SIAM Workshop on Combinatorial Scientific Computing
- 2011-10 Markus Beckers, Viktor Mosenkis, Michael Maier, Uwe Naumann: Adjoint Subgradient Calculation for McCormick Relaxations

- 2011-11 Nils Jansen, Erika Ábrahám, Jens Katelaan, Ralf Wimmer, Joost-Pieter Katoen, Bernd Becker: Hierarchical Counterexamples for Discrete-Time Markov Chains
- 2011-12 Ingo Felscher, Wolfgang Thomas: On Compositional Failure Detection in Structured Transition Systems
- 2011-13 Michael Förster, Uwe Naumann, Jean Utke: Toward Adjoint OpenMP
- 2011-14 Daniel Neider, Roman Rabinovich, Martin Zimmermann: Solving Muller Games via Safety Games
- 2011-16 Niloofar Safiran, Uwe Naumann: Toward Adjoint OpenFOAM
- 2011-18 Kamal Barakat: Introducing Timers to pi-Calculus
- 2011-19 Marc Brockschmidt, Thomas Ströder, Carsten Otto, Jürgen Giesl: Automated Detection of Non-Termination and NullPointerExceptions for Java Bytecode
- 2011-24 Callum Corbett, Uwe Naumann, Alexander Mitsos: Demonstration of a Branch-and-Bound Algorithm for Global Optimization using McCormick Relaxations
- 2011-25 Callum Corbett, Michael Maier, Markus Beckers, Uwe Naumann, Amin Ghoheity, Alexander Mitsos: Compiler-Generated Subgradient Code for McCormick Relaxations

* These reports are only available as a printed version.

Please contact biblio@informatik.rwth-aachen.de to obtain copies.